

参数 Parameter			机型 Model	ZB-7B	ZB-10B			ZB-13B				ZB-17B		
模 数 Model				4S	4S	4SL	4SXL	4S	4SL	4SXL	4SL	4S	4SL	4SXL
产品 Product	规 格 Specificarion		M4 (3/16)	M6 (1/4)			M8 (5/16)				M10 (3/8)			
	最长长度 (mm) The maximum length		40mm	50mm	75mm	100mm	80mm	100mm	150mm	200mm	100mm	150mm	300mm	
	最长长度mm The longest length	外六角螺丝 Outside Hexagon Screw	6	8	12	15	14	20	30	60	16	30	100	
		强力螺丝 Strong screw	8	10	16	20	20	25	40	60	20	40	100	
每分钟稳定产能 Stable capacity per minute			200	180	150	130	170	150	130	80	140	110	70	
最大切断长度 (mm) Maximum cut length			55	70	105	120	105	130	180	240	135	180	350	
最大切断直径 (mm) Maximum cut diameter			5	8		10	10				12			
前托顶出长度 (mm) Front Ejector Length			10	13	15	16	20	23	30	40	20	30	60	
后托顶出长度 (mm) back Ejector Length			45	60	90	110	90	120	175	230	115	175	325	
切模 (mm) cutting die			ø20*30	ø28*46	ø28*46	ø28*46	ø35*56	ø38*79	ø38*79	ø38*79	ø40*66	ø40*80	ø40*100	
公模束仔 (mm) Male Die Clamp			ø32*60	ø40*80	ø40*110	ø40*110	ø45*110	ø45*111	ø45*130	ø45*140	ø10*111	ø50*130	ø50*200	
母模 (mm) Female Die			ø38*60	ø50*65	ø50*105	ø50*130	ø60*105	ø70*135	ø70*185	ø70*225	ø70*135	ø80*185	ø80*330	
母模中心距 (mm) female die center distance			48	60		69	87				93			
主滑板行程 (mm) main slide stroke			100	120	150	150	140	200	250	350	180	250	460	
压造力 (Ton) Press force			15T	40T	40T	45T	65T	65T	70T	70T	85T	85T	90T	
主马达 (kw) Primary motor			7.5kw	11kw	15kw	18.5kw	22kw	18.5kw	22kw	22kw	22kw	30kw	30kw	
机械重量 (kg) Machine weight			4T	8T	9T	12T	13T	17T	18T	19T	18.5T	21T	33T	

参数 Parameter		机型 Model	ZB-198				ZB-248		ZB-308		ZB-368	ZB-418
模 数 Model			4S	4SL	4SXL	4SLL	4S	4SL	4S	4SL	4S	4S
产 品 Product	规 格 Specificarion		M12 (1/2)				M16 (5/8)		M20 (3/4)		M24 (1)	M27 $\frac{1}{8}$ (1)
	最长长度 (mm) The maximum length		100mm	150mm	200mm	300mm	150mm	300mm	200mm	300mm	300mm	300mm
	最长长度mm The longest length	外六角螺丝 Outside Hexagon Screw	20	40	50	100	20	100	40	100	125	100
		强力螺丝 Strong screw	25	40	50	100	35	100	40	100	125	100
每分钟稳定产能 Stable capacity per minute			130	100	90	65	90	65	80	60	55	50
最大切断长度 (mm) Maximum cut length			140	185	240	340	185	340	270	355	370	400
最大切断直径 (mm) Maximum cut diameter			15				18		23		29	34
前托顶出长度 (mm) Front Ejector Length			26	30	35	60	33	60	35	60	60	60
后托顶出长度 (mm) back Ejector Length			120	180	220	325	185	335	240	335	340	340
切模 (mm) cutting die			ø46*80	ø46*80	ø46*80	ø46*80	ø60*100	ø60*100	ø75*120	ø75*120	ø90*140	ø110*140
公模束仔 (mm) Male Die Clamp			ø60*120	ø60*170	ø60*170	ø60*250	ø75*160	ø75*232	ø90*197	ø90*240	ø105*235	ø120*250
母模 (mm) Female Die			ø80*123	ø93*190	ø95*240	ø95*350	ø100*195	ø100*360	ø125*240	ø125*360	ø160*370	ø178*385
母模中心距 (mm) female die center distance			114				126		138		174	195
主滑板行程 (mm) main slide stroke			200	270	340	460	280	500	360	500	500	500
压造力 (Ton) Press force			120T	120T	120T	120T	160T	190T	220T	300T	350T	550T
主马达 (kw) Primary motor			30kw	37kw	37kw	50kw	50kw	75kw	75kw	100kw	100kw	115kw
机械重量 (kg) Machine weight			24T	26T	33T	36T	40T	58T	66T	93T	125T	140T