



**SWAB CUP PACKER**

MODEL: WC-SWCP

PRODUCT No.: WC-11601

This is a moderate performance packer suit for many applications at low cost to hold pressure from below and simultaneously provides an unrestricted liner top at the end of cementing operations. It has two wire meshed Swab Cup Element. This provides extra sealing during setting of liner hanger and cementing job. End connections are furnished with standard or premium connections in compliance with the API standard or as per customer requirements for successful run and installation in the Liner Hanger System.

■ **Specification Guide:**

Casing				Packer		
OD inch	Weight Lb/ft	ID range		Max. OD inch	Min. ID Inch	End Connection Specification inch
		Min. inch	Max. inch			
3 1/2	9.2 - 10.3	2.922	2.992	2.810	1.50	1.900 NU 10RD
4-1/2	9.5 - 13.5	3.920	4.090	3.750	2.00	2 3/8 EU 8RD
	15.1	3.826		3.650	2.50	2 7/8 EU 8RD
5	18	4.276		4.130	2.00	2 3/8 EU 8RD
					2.00	2 3/8 EU 8RD
5-1/2	13 - 20	4.778	5.044	4.625	2.50	2 7/8 EU 8RD
					3.00	3 1/2 EU 8RD
					2.50	2 7/8 EU 8RD
6-5/8	20	6.049		5.750	3.00	3 1/2 EU 8RD
	20-24	5.921	6.049		4.00	4 1/2 EU 8RD
7	20-29	6.184	6.456	6.000	2.00	2 3/8 EU 8RD
					2.50	2 7/8 EU 8RD
					3.00	3 1/2 EU 8RD
					4.00	4 1/2 EU 8RD
7 5/8	24-26.4	6.969	7.025	6.750	2.50	2 7/8 EU 8RD
	29.7-33.7	6.765	6.875	6.375	2.50	2 7/8 EU 8RD
8 5/8	28-36	7.825	8.017	7.735	2.50	2 7/8 EU 8RD
9 5/8	40-47	8.681	8.835	8.450	3.00	3 1/2 EU 8RD
10 3/4	40.5-55.5	9.760	10.050	9.710	4.00	4 1/2 EU 8RD