




iFACE 302



Features

- ✓ Identification modes include Facial recognition, Fingerprint, RFID and/or Password
- ✓ Elegant ergonomic design
- ✓ 4.3" TFT touch screen provides rich user experience and intuitive user interface
- ✓ 6 user-defined function keys
- ✓ Relays for door access control and inputs for door sensor and exit button
- ✓ Relay contact for external scheduled bell
- ✓ Infra-red light source for camera enables face illumination in poorly lit environments
- ✓ Optional built-in battery backup provides approx 4 hours of continuous operation.
- ✓ Optional built-in Wi-Fi or GPRS for wireless communication.
- ✓ Configurable Wiegand Output for connections to 3rd party access control panels

Specification

| | iFace300 | iFace301 | iFace302 | |
|-------------------------------|---|---|--|--------|
| |  |  |  | |
| CPU | ZK Multi-Bio CPU 600 MHz | | | |
| Memory | 256MB Flash, 64MB SDRAM | | | |
| Hardware Platform | ZEM600 Multi-Medium Development Platform | | | |
| Fingerprint Sensor | None | ZK Optical Fingerprint Sensor without coating | | |
| Camera | High Resolution Infrared Camera | | | |
| Display | 4.3" TFT touch screen | | | |
| Face capacity | 700 | 700 | 700 | |
| Fingerprint capacity | none | 3000 | 3000 | |
| ID Card capacity | 10,000 | 10,000 | 10,000 | |
| Logs capacity | 100,000 | 100,000 | 100,000 | |
| Algorithm Version | ZK Face 5.0 | ZK Face 5.0 & ZK Finger 10.0 | | |
| 2000mAh backup battery | Optional | Optional | Optional | |
| Communication | TCP/IP,RS232/485 | | | |
| USB-HOST | Two USB-Host ports | | | |
| Wireless Wi-Fi | Optional | Optional | Optional | |
| Time attendance functions | External Scheduled-bell, Day Light Saving Time Settings, Work Code, Short Message, Optional Webserver | | | |
| Access control interfaces for | 3 rd party electric lock, door sensor, exit button | none | 3 rd party electric lock, door sensor, exit button | |
| Wiegand Signal | Output | none | Output | Output |
| Optional functions | GPRS, Serial Printer, Mifare/HID/iClass card, built-in POE | | | |
| Power supply | 12VDC, 3A | | | |
| Verification Speed | ≤2 sec | | | |
| Operating temp | 0℃- 45 ℃ | | | |
| Operating Humidity | 20%-80% | | | |