DIFFERENTIAL PRESSURE GAUGE DPG-20



SALIENT FEATURES

- Piezo resistive Silicon Sensor
- Measuring Range +/-0.1 to 200 bar
- Indication Through LCD
- Display auto shut off facility
- ➢Battery Operated
- Handy & maintenance free
- ➢ Reliable & cost effective
- Unit Conversion facility
- ➤Zero tare facility

DESCRIPTION



Electronet series DPG-20 are differential pressure gauges for fast, easy & trouble free operation. These can be cost effective & ideal for monitoring the pressure. Display shut-off facility is provided so that display can be made 'ON' only if required through push button. Thus it saves the battery power & results in long lasting battery operation.

TECHNICAL SPECIFICATIONS

Sensor Type Range Display Accuracy Burst Pressure Over Range Protection	: Piezo Resistive : ±0.1 to 200 Bar : 8 x 1 LCD : +/- 0.25% F. S. : 2 times max. Pressure range : 1.5 times of Max. operating pressure
Process Temperature	: 120 °C max
Display Lock	: Display can be made ON by pressing 'ON' Key on front fascia Display ON duration programmable (1 min, 2 min, 5 min & continuous ON)
Power Supply	: 3.6 V, Battery Operated
Battery Back up Time	: 2000 Hrs
Response Time	: < 200 mSec
Temperature Coefficient	: +/- 0.01% per °C
Enclosure Material	: SS / Die cast Aluminium IP-65
Process Connection	: 1) 1/4" NPT
	2) ½" NPT 3) 1/4" BSP 4) ½" BSP
Weight	: 1 kg
Operating Conditions	: Temperature : -20 to 75°C / Humidity : 5 to 95% non condensing

ORDERING INFORMATION

					06	1000 psi
			05	Other	05	300 psi
		04	1/2" BSP	04	100 psi	
		03	1⁄4"BSP	03	30 psi	
	02	Female	02	1⁄2"NPT	02	6 psi
	01	Male	01	1⁄4"NPT	01	2 psi
SERIES	Process connection Type		Process Connection		Pressure range	
DPG-20	Α	01	В	01	С	3

*Due to our continuous product revisions, Design, Specifications and Model Number are subject to change without notice. *Accuracy defined at lab conditions. *Draft Range available on request (±200mmWC)

Authorised Dealer



ments B-501/504, 5th floor, Raunak Arcade, Near THC Hospital, Gokhale Road, Naupada,

Thane(W) 400602. Maharashtra INDIA E-Mail: sales@nkinstruments.com Skype: nitinkelkarskype

Telefax Nos.: 91-22-25301330 / 31 / 32 Web: http://www.nkinstruments.com Gtalk: nkinstruments2006

