



PRODUCT DESCRIPTION

Urja Stripp-Coat is a water based peelable coating can be applied on various surface for corrosion protection and spill-scratch protection.

This peelable coating is suitable for surfaces such as metal jobs, Engines, Automobiles, Glass, Aluminum, Steel, Wood, Bare-Metal, Painted surface and wherever protection of surface is required.

It is non-flammable temporary coating that can be easily removed without cleaning agents and cleaners. It is acrylic co-polymers combination which gives best protection from corrosion due to water or water vapor.

Designed as a fast-drying, temporary coating for parts and equipment, URJA-Stripp-Coat is resistant to sagging and running and it being waterbase system it is environment friendly. URJA-Stripp-Coat is a clear coating that can be tinted in a variety of custom colours.

We can offer this coating in various brilliant colours. Whenever colour coat is required.



USES AND AREA OF APPLICATION

Protection of clean metal surfaces for storage or Shipment
Protection of painted surfaces from physical damage during storage or shipping

Paint booths

Tooling

Highly polished metal surfaces

Minimum 2-Coats are required



FEATURES

Does not leave residual contamination

Water-based, non-flammable

Near zero VOC, contains no co-solvents

Prevents corrosion /oxidation of metals

Provides multimetal protection

Temporary coatings for any outdoor conditions

Fast drying

Nice smooth appearance

In different colors


Easy of application and easy clean

Requires no solvent or paint removers

Simple to dispose off as a solid waste

LIMITATIONS

Since strip-ability depends on application conditions and the type of surface to be protected, testing may be required prior to use. Use 2 coats on porous surfaces Use 2 coats for medium to long term outdoor Protection.



TYPICAL APPLICATION

URJA-Stripp-Coat supplied in any colour as per demand which can be applied by spray, brush, roll, or dip.

Applications include:

Automotive body and frame

Steel sheets

Small parts

Transit coatings

URJA-Stripp-Coat can be used in one or two coats.

To achieve good strippability, the recommended thickness per coat should not be less than 2-mil (50Microns).

Minimum 2-Coats are required



LIMITED WARRANTY

FOR INDUSTRIAL USE ONLY

KEEP OUT OF REACH OF CHILDREN

KEEP CONTAINER TIGHTLY CLOSED

NOT FOR INTERNAL CONSUMPTION

CONSULT MATERIAL SAFETY DATA SHEET FOR

MORE INFORMATION

METALS PROTECTED

Carbon steel

Stainless steel

Cast iron

Aluminum and alloys

Glass

Wood

Plastic

Aluminum

Many more

