

URJA SEALANTS PVT. LTD

Gat no-255A, jyotiba nagar, Opp. National Wave Bridge, Talwade, pune, Maharashtra, Pune-412114. Ph. 020-27472234, 27442234, Fax: 020-27472234. E-mail.: urjasealant@gmail.com

TDS NUMBER: LR/TDS/ 04 Revision Number & Date: 1 Sep 2014

URJA BUTYL SEALANT TAPE TECHNICAL DETAILS



Product Description:-

Butyl sealant is a pressure sensitive sealing strip. It is none vulcanizing and also vulcanizing type

Field of application:-

- Use in flexible assemblies (Roofing, Construction)
- Automotive industries (Excellent insulation to outside temperature, sound, vibration)
- Refrigeration, Telecommunication, Railways, engineering ect.

Product Properties:-

Resistance to Pressure:-

≤ 2 KN/m

• Specific Gravity

1.4

• Penetration

80-120



URJA SEALANTS PVT. LTD

Gat no-255A, jyotiba nagar, Opp. National Wave Bridge, Talwade, pune, Maharashtra, Pune-412114. Ph. 020-27472234, 27442234, Fax: 020-27472234. E-mail.: urjasealant@gmail.com

Butyl Sealant Technical Report

Test (Condition)	Test Method	Observed Value
Specific Gravity	IS 3400 (IX)	1.40
Total Solid content	AS 163:64	99.53
	A CITIM D. 1140	N 1 1
UV Test	ASTM D 1148	No changes observed
(50oc /Distance 12 inch/24)	hrs)	
Visual Observation	ASTM C639	No Sag Observed
(Sag Test @ 4.4oc / 4hrs)	ASTW C037	No Sag Observed
(Sag 1est @ 4.40c / 4111s)		
Visual Observation	ASTM 639	No Sag observed
(Sag Test @ 50oC / 4 hrs)		
Visual Observation		No changes Observed
(@15oC/ 24 hrs)		110 011111900 00001100
Visual Observation		Loss of Tackiness & Blister
(@ 135oC / 1 hrs)		formation observed on Surface
~		0.77
Service Temperature	15 degree celsius	OK
	To 110 degree Celsius	
Weather ability	No discoloration	OK
James desirty	Cracking, Adhesion	=

Instruction for Use:-

Surface Preparation:- The surface must be clean dry and free of dust

Standard Packaging:-

- Available as a rectangular cross section or a round diameter
- Thick 2 mm to 8 mm



URJA SEALANTS PVT. LTD

Gat no-255A, jyotiba nagar, Opp. National Wave Bridge, Talwade, pune, Maharashtra, Pune-412114. Ph. 020-27472234, 27442234, Fax: 020-27472234. E-mail.: urjasealant@gmail.com

- Width 4 mm to 75 mm
- Standard liner:- siliconzed paper

Standard Color:- Black, Grey, White

Self Life - Storage:-

- 8 months, in original unopened packaging and protection from humidity.
- Store in a well ventilated room.

<u>Please note:</u> All information & data in this catalogue are compiled with care and are accurate & true to the best of our knowledge & belief. However, we do not accept any responsibility, liability or claim, legal or otherwise, for any consequential loss or damage, regardless of its nature, arising from the usage of the information or data interpreted from this catalogue.