



Zincolet - 40P

Processing Additives

Composition : Blend of dark aliphatic & aromatic hydrocarbon resins.

Specification : Color : Dark brown to Blackish brown
Appearance : Flakes/Beads
Softening point : 100 ± 5°C
Ash content (2hrs,@850°C) : 2% Max

Dosage :
• 4 – 15phr

Uses and Benefits :

- It improves the homogeneity of polymers blend improving the process behavior.
- It gives very good compound tack.
- Zincolet - 40P is compatible with NR,SBR,NBR,CR,EPDM,BR.
- Zincolet - 40P is useful in blending two polymers with different polarities and viscosities.
- Zincolet - 40P does not harden during vulcanization.
- Zincolet - 40P improves mould flow and extrusion characteristics.

Packing : 25 kg Polylinedpolywoven bag / Polylined paper bag.

Storage stability : Upto 2 years in normal storage conditions.

Approvals : **ROHS/SVHC/PAH**

Handling : Consult material safety data sheet (MSDS) for additional handling information for Zincolet - 40P.

PUKHRAJ ADDITIVES LLP

An ISO 9001:2008 Certified Company

5B, 5th Floor, Diamond House, Plot No. 515, Behind National College,
TPS III, 35th Road, Bandra (W), Mumbai, Maharashtra - 400 050 (INDIA).

Tel: +91-9833538089/+91-22-26494911/26494912/26494913

Email: info@pukhrajzincolet.com Visit us at: www.pukhrajzincolet.com