



Technical Data Sheet

Zincolet - 171

Processing Additives

Composition : Blend of Fatty acid ester and Calcium soap with inorganic fillers.

Specification : Appearance : Creamish to Beige color flakes.
Drop Point : $90 \pm 5^\circ\text{C}$
Ash content : $20 \pm 2\%$

Dosage :

- 1 – 3 phr.

Uses and Benefits :

- Improves flow of compound in transfer, compression and injection moulding.
- Prevents sticking of compounds to mill rolls.
- Gives good mould flow and improves viscosity.
- Reduces internal friction resulting in lowering energy consumption and mixing temperature.

Recommended for -

NR, SBR, EPDM, EVA, As well as thermoplastic Elastomers.

Packing : 25 kg Polylinedpolywoven bag / Polylined paper bag.

Storage stability : Upto 2 years in normal storage conditions.

Approvals : **REACH**

Handling : Consult material safety data sheet (MSDS) for additional handling information for Zincolet- 171.

PUKHRAJ ADDITIVES LLP

An ISO 9001:2008 Certified Company

5B, 5th Floor, Diamond House, Plot No. 515, Behind National College,
TPS III, 35th Road, Bandra (W), Mumbai, Maharashtra - 400 050 (INDIA).

Tel: +91-9833538089/+91-22-26494911/26494912/26494913

Email: info@pukhrajzincolet.com Visit us at: www.pukhrajzincolet.com