

V-7**Horizontal Openwell**

Approx Performance Chart at 2800 RPM, 220 & 415 Volts,
50 Hz Supply, S.S. & C.I. Motor Body Openwell Submersible Pump



V-7 S.S. Body			Price ₹ (Without Panel)		Total Head in Meters																
Model No.	H.P.	STG.	Outlet	Single Phase	Three Phase	10	12	14	16	18	20	22	24	26	28	30	32	34	36	38	40
AP7S-052525	0.5	1	1"x1"	6040/-	-	100	80	55	35	20	-	-	-	-	-	-	-	-	-	-	-
AP7S-103225	1.0	1	1.25"x1"	10600/-	10600/-	250	235	220	200	180	160	130	90	-	-	-	-	-	-	-	-
AP7S-154040	1.5	1	1.5"x1.5"	11400/-	11400/-	280	260	245	225	205	180	160	135	100	50	-	-	-	-	-	-
AP7S-205050	2.0	1	2"x2"	14430/-	14430/-	460	450	425	405	380	355	325	290	240	180	80	-	-	-	-	-
AP7S-306550	3.0	1	2"x2"	15370/-	15370/-	540	530	520	505	485	460	430	405	375	340	290	240	155	-	-	-
AP7S-306565	3.0	1	2.5"x2.5"	15820/-	15820/-	940	840	790	730	670	590	490	370	-	-	-	-	-	-	-	-
AP7S-506550	5.0	1	2.5"x2"	-	16830/-	780	765	755	745	735	725	715	690	670	635	595	525	485	425	350	-
AP7S-506565	5.0	1	2.5"x2.5"	-	16630/-	960	940	930	900	870	810	760	700	640	550	440	-	-	-	-	-

V-7 C.I. Body			Price ₹ (Without Panel)		Total Head in Meters																
Model No.	H.P.	STG.	Outlet	Single Phase	Three Phase	10	12	14	16	18	20	22	24	26	28	30	32	34	36	38	40
AP7C-052525	0.5	1	1"x1"	-	-	100	80	55	35	20	-	-	-	-	-	-	-	-	-	-	-
AP7C-103225	1.0	1	1.25"x1"	-	-	250	235	220	200	180	160	130	90	-	-	-	-	-	-	-	-
AP7C-154040	1.5	1	1.5"x1.5"	-	-	280	260	245	225	205	180	160	135	100	50	-	-	-	-	-	-
AP7C-205050	2.0	1	2"x2"	15150/-	15150/-	460	450	425	405	380	355	325	290	240	180	80	-	-	-	-	-
AP7C-306550	3.0	1	2"x2"	16100/-	16100/-	540	530	520	505	485	460	430	405	375	340	290	240	155	-	-	-
AP7C-306565	3.0	1	2.5"x2.5"	16550/-	16550/-	940	840	790	730	670	590	490	370	-	-	-	-	-	-	-	-
AP7C-506550	5.0	1	2.5"x2"	-	17620/-	780	765	755	745	735	725	715	690	670	635	595	525	485	425	350	-
AP7C-506565	5.0	1	2.5"x2.5"	-	17420/-	960	940	930	900	870	810	760	700	640	550	440	-	-	-	-	-

