

TECHNICAL SPECIFICATION

		SB-4P
CONTROLLER	AXIS TOTAL NO, AXIS MAX SIM AXIS	BOSCH REXROTH MTX-MICOR SP1, SP2, Z, C1, C2, C3, C4, A, B, W, X. 11 AXIS 4 AXIS
MAIN SPINDLE	SPINDLE POWER MAX SEED RPM	HZ 400 W, VER 400 W HZ 10000, VER 14000
BALL SIZE	MM	3 TO 12
TYPES OF BALL		ROUND / CAPSULE / ELLIPSE
FEED AXIS	FEED AXIS A,B,C1,C2,C3,C4,W	1000 DEG/MIN 5000 DEG/MIN
MOTOR TORQUE	B,C1,C2,C3 A,X,Z,C4,W	750 W 400 W
INSTALLED POWER	KW	6 KW, 3 Ø
PNEUMATIC SUPPLY	BAR	6 BAR
DIMENSION	L / B/ H INCH	48 X 48 X 72 INCH
WEIGHT	KG	550 KG

SPECIFICATION

- * The computerised and numerically controlled (CNC) machine is capable of generating various decoration on convex (Oval) surface.
- * The machine is equipped with CNC controller and AC servo motors to ensure lifelong maintenance free working.
- * The CNC controller programs are generated in (G) codes and (M) codes manually.
- * All the machine components are machined on precision CNC machine and are hardened and grounded. These components are individually inspected for the accuracies. The machine is assembled in a controlled environment.



Solanki Mechanic Works

40-W, Bhaktinagar, Udhyanagar, GIDC, Ind. Estate, Rajkot - 360 002 (Gujarat) India.

☎ +91 281 2362189 | 📞 +91 281 2376386

✉ info@soliyo.com • solankimachines@gmail.com | 🌐 www.soliyo.com