



JETEXINDIA

Hydraulic HLP 32, 46, 68, 100

JETEX Hydraulic HLP grades are high performance anti-wear hydraulic oils specially formulated from premium quality solvent refined base oils and high performance additives and have excellent product stability with good anti-wear performance

Application

- Lubrication of industrial machinery
- Hydraulic systems of mobile and construction equipment
- Hydraulic systems fitted with vane, gear or piston pumps
- Plastic injection moulding machines
- Medium duty compressors

Benefits

- Excellent filter life due to superior dry & wet filter ability
- Longer equipment life due to lower wear & tear of aggregates
- Reduced equipment downtime
- Trouble free operation

Performance standards

They exceed the performance requirements of the following standards,

- Denison Hydraulics HF-0
- Eaton M-2950-S & Eaton I-286-S3
- DIN 51524 Part II Class HLP
- Cincinnati Machine P-68,P-69 & P-70

Typical product data

Characteristics	WAAREE Hydraulic HLP 32	WAAREE Hydraulic HLP 46	WAAREE Hydraulic HLP 68	WAAREE Hydraulic HLP 100
ISO VG no.	32	46	68	100
KV, cSt @ 40 °C	29-34	43-48	64-72	95-105
VI , min	100	100	100	100
Flash point(COC) ° C Min	210	220	240	250
Pour Point °C Max	-18	-18	-18	-18

(These are typical figures and do not constitute a specification)

For more information or MSDS please contact your local JETEX Oils sales representative or the nearest distributor/dealer. You may also e-mail us at contact@jetexindia.com or write to us at the address given below.