



Steady Model



Standard Features:

- Safety Valve
- Provision for max. opening feedback
- 1 set swarf guard 3-piece
- Provision for compressed air connection
- Provision for centralized lubrication

	FRUAB3	FRUAB3.1	FRUAB4	FRUAB5	FRUAB6
A	348	356	480	614	829
B	308	316	437	500	709
C	115	123	146	178	215
D	135	135	240	270	330
E	262	262	365	400	610/640
F	290	290	400	450	680
G	85	85	110	145	145
J	52	52	69.5	83	83
K	45	45	60	75	75
L	25	25	25	29	29
M	47	47	52	62	43
N	25	25	32	36	35
O	40	40	43	114	120
P2	74	74	85	85	124
P3	57	57	68	85	91
R	117.5	124	172	209	290
S	18	18	23	23	27
T	199	198	245	325	414
V	91.5	99.5	128	160	182
Y	19	19	19	20	27
U1	12	20	30	48	160
U2	130	165	220	268	460
U1	21	20	30	48	160
U2	130	165	220	268	460
Z	66	76	111	135	230
Z1	62	72	106.5	130	225
d	80	80	100	100	130
e	58	58	68	85	186
f	27	27	39	40	48.5
g	180	180	220	270	
h	1/4"	1/4"	3/8"	3/8"	3/8"
bar	8/60	8/60	8/60	8/80	8/70
daN	1000	1000	1500	2000	3000
daN	250	250	400	400	
mm	0.04	0.04	0.05	0.06	0.06
mm	0.007	0.007	0.007	0.01	0.01
m/min	800	800	720	650	
kg	55	55	115	190	430