



Pioneer Lab Equipments Mfgs. Since - 1975

BACTERIOLOGICAL INCUBATOR (LAB INCUBATOR) MIC-120



STANDARD SIZES AVAILABLE

Size In Inches (In Cms.)	Rating Watts	No. of Shelves
12" X 12" X 12"	750	1
14" X 14" X 14"	1000	2
18" X 18" X 18"	1500	2
18" X 18" X 24"	1750	2
24" X 24" X 24"	2000	2
18" X 18" X 36"	2200	3
24" X 24" X 36"	2500	3

- ☞ Sturdy Unit with Double Walled Construction.
- ☞ Inner Chamber made of S.S. and Outer made of Mild Steel Powder Coated.
- ☞ Gap between the walls fitted with glass wool insulation to avoid heat loss.
- ☞ Heating elements are made of high grade chrome plated nichrome wire.
- ☞ Temperature is controlled by thermostat / Digital Temperature Controller.
- ☞ Temperature range : 5 Deg. C above ambient to 60 Deg. C. Accuracy : +/- 2 Deg. C.
- ☞ Air Ventilation is provided on the top of the unit to remove the hot gases / fumes.
- ☞ Heaters are placed at the bottom side of the unit.
- ☞ All the control switches & pilot lamps are fitted on the front panel.
- ☞ Supplied with G.I. wire mesh Trays.
- ☞ Available in GMP model also.

Manufactured by :
MODERN INDUSTRIAL CORPORATION