



PT-280

Portable Thermal Printer Genuine Quality

Specification	PT-280
Printing mode	Thermal Printing
Dot density	384dot/line
Print speed	60mm/sec(max.)
Paper width	58mm
Paper diameter	50mm(max.)
Interface	USB+Bluetooth(standard), USB+ Double Bluetooth, USB+wifi
Barcode type	UPC-A, UPC-E, EAN(JAN)13, EAN(JAN)8, CODE39, CODEBAR, ITF, CODE93, CODE128, QR CODE
Character font	GB18030/BIG 5/Korean Character. ANK Character: FontA:12*24dot,FontB:9*17dot Korean/Simplified,Traditional Chinese:24*24dot
Print Command	ESC/POS Compatible
Printing Length	50KM
Battery	~800mA- 1900mA, 7.4V rechargeable Li-ion Battery
Power Adapter	Input:AC100-220V Output:DC9V/1A
Charging time	Around 3 hours
Buffer	Input buffer 4K bytes NV Flash 60K bytes
Dimension	~48.5mm(L)x86mm(W)x58.5mm(H)
Weight	288g
Work Environment	~temperature: 0~45°C , Humidity: 10 ~ 80%
Storage Environment	~temperature: -10 ~ 60°C , Humidity: 10 ~ 90%

PT-280 Portable Thermal Printer



Handheld comfort, can be linked to the chest
You can clip the waist;



Easy paper loading, easy to use;
Classic three-button,



USB Bluetooth interface (standard),
USB + WIFI interface (optional);



LED indicates the printer abnormal, electricalThe amount of state charged with communication connections.