



MICRO OHM METER DOT 401



Key Features:

- Range: 0.10μΩ- 20 KΩ, in 8 ranges
- Max test current: 1 A
- 4½ Digit LED display/19999 counts
- Gold plated Kelvin probe/4 wire method
- Over Range Indication
- Zero adjust and 2000uΩ adjust feature for lowest range
- Metal Cabinet

Technical Specifications

DISPLAY	4 ½ digits LED 0.5" height, max display 19999 counts							
RANGE	2000μΩ	20mΩ	200mΩ	2000mΩ	20Ω	200Ω	2000Ω	20KΩ
RESOLUTION	0.1μΩ	0.001mΩ	0.01mΩ	0.1mΩ	0.001Ω	0.01Ω	0.1Ω	0.001KΩ
CURRENT	1A	1A	100mA	10mA	10mA	1m A	1mA	100μA
ACCURACY	0.08% + 8 digits	0.03% + 4 digits						
OVER RANGE INDICATION	Display starts blinking							
MEASUREMENT SYSTEM	4 terminals gold plated Kelvin probe avoids lead & contact resistance							
POWER REQUIREMENT	230 +/-10% VAC, 50 Hz, single phase							
CABINET SIZE	70 mm (H) x 260 mm (W) x 300 mm (D). Elegant cabinet with tilt position							
WEIGHT	4.0 Kgs. Approx.							
Supplied with Gold Plated Kelvin test leads , mains cord, spare fuse, and operating manual								

[ClickForBackToTOC](#)

DOT TECHNOLOGIES

(An ISO 9001:2015 Certified Company)

25, Victoria Road, Victoria Layout, Bangalore-560047 INDIA; Email: sales@dottech.in, info@dottech.in; web: www.dottech.in
Phone: +91 8970010661 /+91 7483641565