

Specifications

Model Comparison

Y-30T	IPAP: 4 - 30 hPa EPAP: 4 - 25 hPa CPAP mode: 4 - 20 hPa	3.5-inch	CPAP, S, T, S/T
-------	---	----------	-----------------

General Info

Dimensions: 170 mm × 180 mm × 118 mm

290 mm × 180 mm × 134 mm (with the humidifier)

Weight: 1.5 kg

2.5 kg (with the humidifier)

Water capacity: 350 mL at recommended water level

Ramp

The ramp time ranges from 0 to 60 minutes

Humidifier

Humidifier Settings: off, 1 to 5 (95°F to 167°F / 35°C to 75°C)

Humidifier Output: No less than 10 mg H₂O/L

SpO₂

Range: 0 to 100%

Pulse Rate

Range: 40 to 240 BPM

Sound Pressure Level

< 30 dB, when the device is working at the pressure of 10 hPa

Storage

SD card can record patient data and fault information

AC Power Consumption

100 - 240 V AC, 50/60 Hz, Max 2 A

Key Parameters

Target Vt: On/ Off

150~1500 mL

Reslex: Patient, Off, 1~3

I Sens.: 1~8

E Sens.: 1~8

Res Rate: 3~40 BPM

Ti: 0.3-3.0s

Rise Time: 1~4



BMC Medical Co., Ltd.

Room 110, Tower A Fengyu Building, No.115 Fucheng Road, Haidian,
100036 Beijing, PEOPLE'S REPUBLIC OF CHINA

Tel: +86-22-8293 9881 / Fax: +86-22-8293 9881 ext. 810

en.bmc-medical.com