

Description

Fiber Glass Mesh is a ready-to-use mesh which is thin, strong and flexible alkali resistant for embedment with waterproofing and crack-isolation membrane on both the residential and commercial floors & walls of sunk portions and top roof terrace.

Fiber Glass Mesh improves the performance of building near water bodies when applied over cracks, coves and corners and around drains.

Advantages

Durable and flexible
Easy embedment
Easy in installation
Ready to use
Easy to cut with knife or scissors

Uses

In kitchen wash area
Terrace or roof area
Areas near water bodies
where hydrostatic pressure exist
To repair patches of floors, ceiling and rendering walls
Toilet bathroom and sunken portion

Storage

Minimum of 2 years shelf-life if kept under room temperature (i.e. 27°C). It should kept away from direct sunlight and store in cool and dry place.

Process of application.

After applying first layer of waterproofing as per the requirements by using appropriate equipment.

Lying of the net over the first coat of the application done, positioning it in the vertical or horizontal directions and overlapping the joints by at least 10 cm.

Level the surface properly It is advisable to add strips of net sloping at 45° on a level with windows and door openings. If waterproofing integrity is required in expansion and control, Points net strip can be bond on two sides of joint and seal it.

Technical Information

PROPERTIES	RESULTS
Appearance	White colour glass fiber
Weight	45 gm/meter square
Thickness	0.012"(0.3mm)
Weave	Leno
Application temperature	-20°C to +45°C

Benefits

Compatibility:

It has excellent compatibility with all cement- or epoxy-based mortars.

User friendly:

specifically developed to provide an easy to apply product.

Definable performance:

positive benefits are easily demonstrated via a single and simple measurement.

Packaging

Fiber Glass Mesh is supplied in 50 meters rolls.