

SAVEMA 20 i&c&tr SERIES THERMAL TRANSFER OVERPRINTERS

32*40 I
53*40 I
Magnetic



Common Specifications for All Printers

Software: SAYASIS Template Design (Date and Time, Custom Formatted Date and Time, Text, Text Block, Merge Fields, Database Support, Counter, Logo, 1D / 2D Barcodes, GS-1 Barcodes, Table Creation Support and User-Friendly Interface)

Windows Driver Support, Teklynx Software (Code-soft, Labelview and Label Matrix Support), Emulator Support, Printer Management with SPPL (Savema Protocol) Commands, Printer Control with Remote Control)

Barcodes: 1D Barcodes (EAN-13, EAN-8, CODE 128, CODE 39, CODABAR, ITF 2of5, ITF 14, UPC-A, UPC-E ...), 2D Barcodes (Datamatrix, QR Code, PDF417, Aztec code...), GS-1 Barcodes (GS1-128, GS1-Datamatrix, GS1-Databar Barcodes)

Resolution: 300dpi (12 dots/mm) horizontally and vertically

Operating Temperature: 5 °C - 40 °C (41°F-104°F)

Memory: 5000 Template Storage Capacity, 1GB Internal Memory, Up to 16GB SD Memory Card Support, Up to 32GB USB Memory Support

| Specifications | 32*40 I (Intermittent) | 53*40 I (Intermittent) |
|------------------------|---|---|
| Print Area | 32mm x 40mm | 53mm x 40mm |
| Print Speed | 50 - 300 mm/sec | |
| Production | 100 prints/min. | |
| Ribbon Widths & Length | 22mm, 35 mm (0,9" - 1,4") & 600 meters (656yards) loaded ribbon | 35mm, 55 mm (1,4" - 2,2") & 600 meters (656yards) loaded ribbon |
| Power Supply | 100/240V 50/60 Hz | |
| Air Supply (Bar) | Magnetic / Don't Need Air | |
| Input/Outputs | Print signal / Fault signal, Busy signal. | |
| Output Messages | Update Error, Contact Error, Ribbon Break / Not Found Error, Remaining Ribbon Quantity, Number of Printed Templates, Number of Prints per Minute | |
| Connection Types | Relay(NPN, PNP) - Photocell (NPN, PNP) | |
| Communications | RS-232, Ethernet, USB | |
| Ribbon Save Modes | Vertical & Horizontal Ribbon Save Modes | |
| Advanced Control | 4.3" Touch Screen Control, Template Changing while Running, Print Position Adjustment, Contrast, Print Delay, Template-Specific Adjustment, Internal Contact Signal, Multi-print Contact Signal, Template Shifting, Template Rotation | |
| Operator Interface | 4.3" 272x480 Pixels Resolution, Full-color display, Password protection on menus, Multi-language(18) support | |
| Weight (Printer) | 5,6 Kg. | |
| Dimensions | 175mm H x 190mm W x 197mm D | 175mm H x 190mm W x 210mm D |

