

# SELF PROPELLED VERTICAL LIFTS (BATTERY OPERATED)



## Standard equipment

- ◆ Proportional controls
- ◆ Automatic Pothole Protection
- ◆ 2WD
- ◆ Emergency lowering system
- ◆ Emergency stop button
- ◆ Onboard diagnostic system
- ◆ Tilt sensor with alarm
- ◆ Low volt age alarm
- ◆ Horn
- ◆ Hour meter
- ◆ Forklift pockets
- ◆ Charger protection
- ◆ Charge indicator
- ◆ Flashing beacon
- ◆ Can Bus Technology
- ◆ Controller languages choose



## Parameter table

SPECIFICATION	GTWZ7.501	GTWZ601
Load capacity	125KG	125KG
Extended platform Load	90KG	90KG
Working height	9.5m	8m
Platform height	7.5m	6m
Overall height	2.00m	1.92m
Overall width	0.8m	0.8m
Overall length	1.36m	1.36m
Maximum slope	1.5-3°	1.5-3°
Grade ability	30%	30%
Maximum Drive Speeds-Stowed	4Km/h	4Km/h
Maximum Drive Speeds-Raised	1.1Km/h	1.1Km/h
Ground clearance	0.02m	0.02m
Wheelbase	1.17m	1.17m
Front wheels	8in	8in
Drive wheel	∅ 250*80	∅ 250*80
Platform size	0.78*0.70m	0.78*0.70
Platform extension size	0.56m	0.56m
Self Weight	880KG	850KG
Batteries	2-12V/120Ah	2 12V/120Ah
Integrated charger	24V/15A	24V/15A
Drive motors	2-24V/0.5KW	2-24V/0.5KW
Lifting motor	24VDC/1.5KW	24VDC/1.5KW
Up/Down speed	48/40sec	43/35sec

