

# ALUMINIUM VERTICAL SINGLE MAST LIFT



## Standard equipment

- ◆ Leveling outrigger device
- ◆ Two controllers operation
- ◆ Emergency stop button
- ◆ Emergency lowering system
- ◆ Overloading limited
- ◆ Battery charge indicator
- ◆ Limit switch



## Parameter table

Model	GTWY601	GTWY801	GTWY1001
Capacity (kg)	150	125	125
Max Platform height H1(m)	6	8	10
Max working height H2 (m)	8	10	12
Platform size (m)	0.63x0.64	0.63x0.64	0.63x0.64
Overall length A (m)	1.42	1.42	1.42
Overall width B (m)	0.82	0.82	0.82
Overall height H3(m)	1.92	2.00	1.90
Outrigger Footprint(L/W)	1.90x1.75	1.90x1.75	1.90x1.75
Ground clearance (m)	0.06	0.06	0.06
Wheelbase	1.11	1.11	1.11
Front wheels size (inch)	5	5	5
Rear wheel (inch)	8	8	8
Battery	2-12V/65Ah	2-12V/65Ah	2-12V/65Ah
Integrated charger	12V/15A	12V/15A	12V/15A
Lifting motor (AC)	110-230V/0.75KW	110-230V/0.75KW	110-230V/0.75KW
Lifting motor (DC)	12V/0.75KW	12V/0.75KW	12V/0.75KW
Lifting time (S)	38	44	46
Lowering time (S)	35	38	40
Self weight (kg)	415(AC) 450(DC)	450(AC) 485(DC)	490(AC) 525(DC)

