JAS ASSOCIATES

J150NRO Technical Specification

Product Image



Model	J150NRO
Dispenser Flow Rate	150 liters/Hr
Storage Tank-HOT-Water	
Storage Tank-Cold-Water	
Storage Tank-Normal Water	80 Liters
No. of Faucets	2 or 3 or 4
Heater Power in Watts	
Cooler Power in Watts	
Nett Weight in Kg (Approx)	68

Water Purification Technology	RO
Inlet Water TDS Recommended	Borewell Water- 300PPM to 1800PPM(Max)
Purification Stages	Fine Sediment Filter, Activated Carbon Filter, RO Membrane, Post Carbon Filter, UV(Optional)
Input Water TDS Rejection	90%
Recovery	30-40%
Power Supply (AC 50Hz)	180 to 240 V AC/50 Hz
Control Type	Float Switch /Float Valve
MOC-Housing	Stainless Steel 202 Grade -0.8 mm thick
MOC-Normal Storage Tank	LLDPE or SS304 Grade-0.8mm thick
MOC-Hot Storage Tank	
MOC-Cold Storage Tank	
MOC-Faucets	Brass Chromium plated
MOC-Heater Coil	
MOC-Drip Tray	Stainless Steel 304Grade-0.8mm thick
MOC-Leg	Stainless Steel 304Grade-2mm thick
MOC-Rear Cover	Stainless Steel 202 Grade -0.8 mm thick
Cooling Temperature Range	
Heater Temperature Range	
Condenser Tubing	
Insulation of Cooling Tank	
Compressor Make	
Compressor Refrigerant	
Dimension-Model	L-530mm, B-560mm , H-1475mm

Contact Details

Website: https://jasassociates.org