

WinnerOne

Comfort Acrylic Distemper



HomeCoat Comfort Acrylic Distemper is an acrylic water-based, interior wall finish. It is value for money product to have beautiful walls at affordable price. Proprietary acrylic binder used in the product gives the distemper excellent hardness in all-weather conditions along with resistance to salty surfaces and good color retention.




WATER BASED



Key Features



Brilliant white tone



Excellent hiding & coverage



Excellent Color Development



Matt finish



Easy wash ability with wet cloth for stain removal.



Acid & Alkali Resistance



Smooth finish



Technical Data

Property	Data
Covering**	The coverage on smooth primed masonry surface with the recommended application procedure is: painting (1 coat): 100 sqfts/kg,
Gloss/Sheen Levels	Matt
PH	8 to 9
Thinning	50% by volume with water
Drying Time	Dry to touch 30 minutes
Shelf Life	Minimum 1 year in original tightly closed containers away from direct sunlight and excessive heat
Pot Life	Use within 24 hrs
Recommended Method	Interior Primer : 1 Coat Acrylic Putty : 2 Coats Interior Primer : 1 Coat Comfort Distemper: 2 Coats

**Actual coverage may vary on factors such as substrate porosity, method of application etc. It is advisable and strongly recommended to check the covering on respective surface before use.



Pack Sizes and Shade Range

Pack Size Availability :- 2 Kg, 5 Kg, 10 Kg, 20 Kg

Shade :- Available in Wide Shade Range

✓ Substrate Suitability

Home Coat's WinnerOne Comfort Distemper is compatible to the following substrates



Asbestos sheets



Concrete



Plaster



Surface preparation

- ✓ Ensure that the surface to be painted is free from any loose paint, dust or grease.
- ✓ Any previous growth of fungus, algae or moss needs to be removed thoroughly by vigorous wire brushing and cleaning with water.
- ✓ On fungus affected areas apply a coat of 'Bio Wash' solution.
- ✓ Allow it to dry for 4-6 hours and then wash with water.
- ✓ Sand the surface with emery paper 180 and wipe clean.



Direction for use

- ✓ Apply a coat of WinnerOne Water primer and allow drying for 6-8 hrs. Smoothen the surface by filing dents with thin coats of acrylic putty and allow drying of 4-6 hrs.
- ✓ Sand the surface with emery paper 180 and wipe it clean.
- ✓ Apply another coat of primer and allow it to dry for 6-8 hours. Sand the surface with emery paper 320 and wipe it clean.
- ✓ Thin 1 kg of Comfort Acrylic Distemper with 500-600 ml of water. Add water slowly to the paste while continuing to stir the mixture.
- ✓ Apply 2-3 coats of paint, with an interval of 6-8 hours between successive coats.



Precautions

- ✓ Prior to use, read and follow product specification, MSDS and label information.
- ✓ Do not over thin
- ✓ Do not apply WinnerOne Acrylic Putty in the form of single coat or thick layer application.
- ✓ Avoid contact with eyes and skin.
- ✓ Use safety equipment like rubber or polythene gloves, safety goggles / glasses and face masks



HomeCoat OPC Pvt. Ltd.

📍 **Factory:** A10, Balaji Industrial Estate, Tondre, Talaja MIDC, Panvel 410206

📍 **Reg. Office :** 101, PrabhuKripa, Plt no 10&12, Rd no 13, Sect 19, New Panvel, Raigad 410206

☎ **8260013001** ✉ connect@homecoat.in 🌐 www.homecoat.in