


WinnerOne

Comfort Acrylic Water Primer

HomeCoat's WinnerOne Comfort Acrylic Water Primer is recommended as a base coat for interior & exterior surfaces. It is water thinnable & formulated to seal the base surface, so as to accept the topcoat easily & to protect the substrate & give an elegant look to the walls. Proprietary acrylic binder used in the product gives excellent penetration and superior adhesion even on moist surfaces. It gives all round protection in all-weather conditions along with resistance to salty surfaces.



 WATER BASED




Key Features



High penetration power & retains a strong grip on the wall surface



Quick Drying



Excellent hiding & coverage



Acid & Alkali Resistance



Superior adhesion on normal & moist surfaces




Technical Data


Property	Data
Covering**	120– 150 sq-ft per ltr for per coat
Colour / Finish	White / Smooth
Recommended DFT	15 - 20 microns per coat
PH	8 to 9
Thinning	50% by volume with water
Shelf Life	12 months when stored in cool & dry place in original sealed container
Top Coat	Compatible to all the existing acrylic top coating systems (viz. Distemper, Plastic Paint, etc)
Recommended Method	Comfort Primer : 1 Coat Acrylic Putty : 2 Coats Comfort Primer : 1Coat Interior Paint : 2 Coats

**Actual coverage may vary on factors such as substrate porosity, method of application etc. It is advisable and strongly recommended to check the covering on respective surface before use.



Pack Sizes and Shade Range

 Pack Size Availability :- 1 ltr, 4 ltr, 10 ltr, 20 ltr

 Shade :- White



Substrate Suitability

Home Coat's WinnerOne Comfort Water Primer is compatible to the following substrates



Asbestos sheets



Concrete



Plaster



Surface preparation



• Scratch the surface properly before applying the primer



• Ensure that the substrate to be painted is free of any dirt, dust, oil, grease, any algal/fungal growth or any other type of contamination



• In case of pre-painted surfaces - loose old paint etc. should be thoroughly removed.



Direction for use



Sand the surface with emery paper 180 and wipe clean.



For Freshly Plastered Surface, apply 1 Coat of Comfort Water Primer by diluting 50% of water.



Allow the primer to dry for 3-4 hrs before application of recommended system on top of primer.



Precautions



Prior to use, read and follow product specification, MSDS and label information.



Do not over dilute or over extend the brush



Stir Well Before Use



Avoid contact with eyes and skin.



Use safety equipment like rubber or polythene gloves, safety goggles / glasses and face masks



HomeCoat OPC Pvt. Ltd.

📍 **Factory:** A10, Balaji Industrial Estate, Tondre, Talaja MIDC, Panvel 410206

📍 **Reg. Office :** 101, PrabhuKripa, Plt no 10&12, Rd no 13, Sect 19, New Panvel, Raigad 410206

☎ **8260013001** ✉ connect@homecoat.in 🌐 www.homecoat.in