

WinnerOne

Reliable Acrylic Distemper



HomeCoat Reliable Acrylic Distemper is an acrylic water-based, interior wall finish. Proprietary acrylic binder used in the product gives the distemper excellent hardness in all-weather conditions along with resistance to salty surfaces and good color retention. This product has higher coverage and longer paint life.



WATER BASED



Key Features



Brilliant white tone



Excellent hiding & coverage



Excellent Color Development



Matt finish



Smooth finish



Improved durability & life



Acid & Alkali Resistance



Easy wash ability with wet cloth for stain removal.



Superior adhesion on normal & moist surfaces



Technical Data

Property	Data
Covering**	150/160 sqfts/kg,
Gloss/Sheen Levels	Matt
PH	8 to 9
Thinning	50% by volume with water
Drying Time	Dry to touch 30 minutes
Shelf Life	Minimum 1 year in original tightly closed containers away from direct sunlight and excessive heat
Pot Life	Use within 24 hrs
Recommended Method	Interior Primer : 1 Coat Acrylic Putty : 2 Coats Interior Primer : 1 Coat Comfort Distemper: 2 Coats

**Actual coverage may vary on factors such as substrate porosity, method of application etc.



Pack Sizes and Shade Range

Pack Size Availability :- 2 Kg, 5 Kg, 10 Kg, 20 Kg

Shade :- Available in Wide Shade Range

✓ Substrate Suitability

Home Coat's WinnerOne Reliable Distemper is compatible to the following substrates



Asbestos sheets



Concrete



Plaster



Surface preparation

- ✓ Ensure that the surface to be painted is free from any loose paint, dust or grease.
- ✓ Any previous growth of fungus, algae or moss needs to be removed thoroughly by vigorous wire brushing and cleaning with water.
- ✓ On fungus affected areas apply a coat of 'Bio Wash' solution.
- ✓ Allow it to dry for 4-6 hours and then wash with water.
- ✓ Sand the surface with emery paper 180 and wipe clean.



Direction for use

- ✓ Sand the surface with emery paper 180 and wipe clean.
- ✓ Apply a coat of WinnerOne Water primer and allow drying for 6-8 hrs. Smoothen the surface by filing dents with thin coats of acrylic putty and allow drying of 4-6 hrs.
- ✓ Sand the surface with emery paper 180 and wipe it clean.
- ✓ Apply another coat of primer and allow it to dry for 6-8 hours. Sand the surface with emery paper 320 and wipe it clean.
- ✓ Thin 1 kg of Reliable Super White Acrylic Distemper with 500-600 ml of water. Add water slowly to the paste while continuing to stir the mixture.
- ✓ Apply 2-3 coats of paint, with an interval of 6-8 hours between successive coats.



Precautions

- ✓ Prior to use, read and follow product specification, MSDS and label information.
- ✓ Do not over thin
- ✓ Do not apply WinnerOne Acrylic Putty in the form of single coat or thick layer application.
- ✓ Avoid contact with eyes and skin.
- ✓ Use safety equipment like rubber or polythene gloves, safety goggles / glasses and face masks



HomeCoat OPC Pvt. Ltd.

📍 **Factory:** A10, Balaji Industrial Estate, Tondre, Talaja MIDC, Panvel 410206

📍 **Reg. Office :** 101, PrabhuKripa, Plt no 10&12, Rd no 13, Sect 19, New Panvel, Raigad 410206

☎ **8260013001** ✉ connect@homecoat.in 🌐 www.homecoat.in