

Reliable TuffBeYouty Rustic Finish Texture

A decorative and protective exterior coating, this synthetic grooved finish is based on copolymer emulsion reinforced by quartz aggregate. It also has 3 more variants namely Vertical, Circular & Angular.



Vertical



Horizontal



Rainfall



Key Features



Anti-Algae,
Anti-Fungal
protection



Superior
adhesion on
normal & moist
surfaces



Plaster
Protection



Improved
durability
& life



Acid & Alkali
Resistance



Quick
Drying



Hides surface
undulation &
fine Cracks



Technical Data

Property	Data
Colour / Finish	Base Colors White / Texture
Recommended DFT	2-3 mm
Solids	86.00 ± 2%
PH	8 to 9
Specific Gravity kh/ltr	2.0±0.05
Theoretical Spreading Rate	2 -2.5 sq ft per kg per coat
Shelf Life	12 months when stored in cool & dry place in original sealed container
Top Coat	Compatible to all the existing acrylic top coating systems (viz. Distemper, Plastic Paint, etc)
Drying Time @ 30oC	Temperature, humidity, air movement, film thickness and number of coats all affect the drying time.
Touch Dry (hours)	1
Dry to recoat (hours)	16-18
Recommended Method	Reliable Primer : 1 Coat Rustic Finish : 1 Coats Acrylic Emulsion : 2 Coat



Pack Sizes and Shade Range

Paintbrush icon Pack Size Availability :- 2 kg, 5 Kg, 10 kg, 20 Kg

Paintbrush icon Shade :- White



Substrate Suitability

Home Coat's Tuff BeYouty Rustic Finish Texture is compatible to the following substrates



Asbestos sheets



Concrete



Plaster



Surface preparation



Ensure that the surface to be painted is free from any loose paint, dust and grease.



Any previous growth of fungus, algae or moss needs to be removed thoroughly by vigorous wire brushing and cleaning with water.



On fungus affected areas apply a coat of 'Bio Wash' solution. Allow it to dry for 4-6 hours and then wash with water



Direction for use



For freshly plastered surface, apply 1 coat of Reliable Acrylic Water Primer by diluting 1 ltr of primer with 500 ml of water.



Allow the primer to dry for 3-4 hours before application of texture finish.



For freshly plastered surface, apply 1 coat of Tuff BeYouty Rustic finish by trowel. Add 3-5% water depending on application requirement.



Allow the texture to dry for 16-18 hrs.



Apply 2 coats of WinnerOne Reliable Exterior Emulsion as top coat (recommended).



Precautions



Prior to use, please use, read and follow product specifications, MSDS and label information.



Do not over thin.



Avoid contact with eye and skin.



Use safety equipment such as rubber gloves and safety goggles.

