



## CNG 2T

Low Smoke 2-Stroke Motorcycle oil

### PRODUCT DESCRIPTION

LUBXTAR CNG 2-T is formulated from premium quality base stocks, high performance additive for engine protection, cleanliness and low smoke in 2-stroke motorcycle/scooter engines even under severe operating conditions.

### APPLICATIONS

Recommended for 2-stroke motorcycle/scooters.  
Suitable for both oil-injection and premix lubrication system; follow manufacture's recommendations for oil to fuel ration.

### FEATURES & BENEFITS

- Outstanding lubricates protects against piston scuffing and premature wear of engine components.
- Advanced formulation provides excellent control against engine deposits and extended engine life.
- Easy miscibility with gasoline ensures stable homogeneous mixture even at low ambient temperatures.
- Low ash additive technology prevents pre-ignition and spark plug fouling

### SPECIFICATION & TYPICAL PROPERTIES

SAE Viscosity Grade		2T
Mets the following specifications		
API TC,JASO FC,JASO FD		x
Typical Properties		
Test Parameters	ASTM Method	Typical values
Viscosity @100°C,cst	D 445	48-70
viscosity Index, Min	D 2270	x
Flash Point,°c,Min	D 92	85
Pour Point,°c,Max	D 97	-15
TBN ,mg KOH/g	D 2896	1.4
Sulphated Ash,%wt,Max	D 874	0.25

Manufactured by :

**LUBXTAR INDUSTRIES PRIVATE LIMITED**

Survey No.92,Gharat wadi,Near Khan Compound, Pelhar,

Vasai East, Mumbai Maharashtra -401208.

Customer Care No.: +91 8780097367

Email : lubxtarindustries@gmail.com

web.www.lubxtar.com

