



ATF-TQ-A

Automatic Transmission fluid

PRODUCT DESCRIPTION

LUBXTAR ATF-TQ-A premium quality transmission oil, blended from high quality solvent refined base stocks, fortified with carefully selected additives, to give good dispersant, oxidation stability, seal compatibility, antifoam, anticorrosion and anti-war characteristics.

APPLICATIONS

Lubrication of synchromesh gears and automatic and power steering units of automobiles and LCVS requiring Type Suffix A fluid

FEATURES & BENEFITS

- High thermal and oxidation stability.
- Provides excellent power shift transmission, even at low temperature.
- Reduces gear wear.
- Improves life of transmission & steering system.
- Compatible with various types of seal materials

SPECIFICATION & TYPICAL PROPERTIES

Grade	ATF-TQ-A	
Mets the following specifications		
SUFFIX 'A'	x	
Typical Properties		
Test Parameters	ASTM Method	Typical values
Specific Gravity @ 15 °C	D 4052	0.878
Viscosity @40°C,cst	D 445	39.0
Viscosity @100°C,cst	D 445	7.3
viscosity Index, Min	D 2270	154
Flash Point(COC), °C, Min	D 92	204
Pour Point , °C, Max	D 97	-42
Colour	D 1500	RED

Manufactured by :

LUBXTAR INDUSTRIES PRIVATE LIMITED

Survey No.92,Gharat wadi,Near Khan Compound, Pelhar,

Vasai East, Mumbai Maharashtra -401208.

Customer Care No.: +91 8780097367

Email : lubxtarindustries@gmail.com

web.www.lubxtar.com

