



## GEARTECH-680

Industrial Gear oil

### PRODUCT DESCRIPTION

LUBXTAR GEARTECH-680 is manufactured from high quality base stocks fortified with extreme pressure additives, anti-foam, anti-rust, and anti-oxidation agents; thereby they have excellent oxidation resistance and thermal stability

### APPLICATIONS

Recommended for suitable for heavily loaded bearings where straight mineral oil do not have sufficiently high film strength to provide effective lubrication.

### FEATURES & BENEFITS

- High viscosity index.
- Good oxidation resistance and thermal stability.
- Excellent corrosion resistance to prevent rusting and corrosion
- Resistance of foaming.
- High thermal stability.

### SPECIFICATION & TYPICAL PROPERTIES

ISO Viscosity Grade	680	
Mets the following specifications		
IS: 8406 -1993	x	
Typical Properties		
Test Parameters	ASTM Method	Typical values
Viscosity, cst@40°C	D 445	625- 700
Viscosity Index, Min.	D 2270	90
Flash Point (COC) °C, Min	D 92	230
Pour Point, °C, Max.	D 97	(-)3
Timken OK load ,KG		60
FZG, Rig Test, Passes		12

Manufactured by :

**LUBXTAR INDUSTRIES PRIVATE LIMITED**

Survey No.92,Gharat wadi,Near Khan Compound, Pelhar,

Vasai East, Mumbai Maharashtra -401208.

Customer Care No.: +91 8780097367

Email : lubxtarindustries@gmail.com

web.www.lubxtar.com

