



## HYDRAULIC-46 (AW)

### Circulation oil

### PRODUCT DESCRIPTION

LUBXTAR HYDRAULIC-46 blended from high quality, chemically-stable solvent refined base oils and incorporated with balanced additive system which include anti wear and oxidation inhibitors. Utilization of Hydraulic Oils (AW) will provide excellent wear protection in hydraulic and circulation systems and good air release properties.

### APPLICATIONS

Recommended for use most types of hydraulic systems, moderately-loaded gears and bearing lubricated by circulation and bath and ring oiling.

### FEATURES & BENEFITS

- Excellent anti-wear performance.
- Provide rust and corrosion protection.
- Low friction.
- Excellent water separation, air release and antifoam properties.
- Hydrolytic stability.

### SPECIFICATION & TYPICAL PROPERTIES

ISO Viscosity Grade		46
Mets the following specifications		
DIN 51524 (Part II), Denison HF -O, HF-2		x
Typical Properties		
Test Parameters	ASTM Method	Typical values
Specific Gravity @ 15 °C	D 4052	0.879
Viscosity @40°C, cst, Min	D 445	46.0
Viscosity @100°C, cst, Max	D 445	6.9
viscosity Index, Min	D 2270	102
Flash Point(COC), °C, Min	D 92	210
Pour Point , °C, Min	D 97	-9
Neutralization No. mg KOH/g	D 974	1.5

Manufactured by :

**LUBXTAR INDUSTRIES PRIVATE LIMITED**

Survey No.92,Gharat wadi,Near Khan Compound, Pelhar,

Vasai East, Mumbai Maharashtra -401208.

Customer Care No.: +91 8780097367

Email : lubxtarindustries@gmail.com

web.www.lubxtar.com

