



GEL GREASE

Universal Lithium Complex EP Grease

PRODUCT DESCRIPTION

LUBXTAR GEL GREASE is lithium complex thickened lubricating grease based on mineral oil and contains antioxidants, corrosion inhibitors and EP additives.

APPLICATIONS

Recommended for all types of operating conditions, but particularly where the operation temperature is high and the use of conventional lithium greases is limited.

FEATURES & BENEFITS

- High viscosity index.
- Good oxidation resistance and thermal stability.
- Excellent corrosion resistance to prevent rusting and corrosion
- Resistance of foaming.
- High thermal stability.

SPECIFICATION & TYPICAL PROPERTIES

ISO Viscosity Grade	680	
Mets the following specifications		
IS: 8406 -1993	x	
Typical Properties		
Test Parameters	ASTM Method	Typical values
Viscosity, cst@40°C	D 445	625- 700
Viscosity Index, Min.	D 2270	90
Flash Point (COC) °C, Min	D 92	230
Pour Point, °C, Max.	D 97	(-)3
Timken OK load ,KG		60
FZG, Rig Test, Passes		12

Manufactured by :

LUBXTAR INDUSTRIES PRIVATE LIMITED

Survey No.92,Gharat wadi,Near Khan Compound, Pelhar,

Vasai East, Mumbai Maharashtra -401208.

Customer Care No.: +91 8780097367

Email : lubxtarindustries@gmail.com

web.www.lubxtar.com

