



HOT ROLLING OIL

HOT Rolling Oil

PRODUCT DESCRIPTION

LUBXTAR hot rolling oil is premium quality rolling oil blended from refined mineral oils and selected additives for use in rolling sheets.

APPLICATIONS

Recommended for use hot rolling mill of steel, copper, aluminum, etc.

FEATURES & BENEFITS

- Reduction in Rolling Mill Power.
- Improved quality of surface finish.
- Increased Roll Life.
- Good oxidation stability.

SPECIFICATION & TYPICAL PROPERTIES

Grade	Hot Rolling oil	
Mets the following specifications		
	x	
Typical Properties		
Test Parameters	ASTM Method	Typical values
Viscosity @100°C, cst, Max	D 445	14
viscosity Index, Min	D 2270	113
Flash Point, °c, Min	D 92	210
Pour Point, °c, Min	D 97	0
Saponification Value mg KOH/gm		90
Free Fatty Acid (as oleic acid) %		3

Manufactured by :

LUBXTAR INDUSTRIES PRIVATE LIMITED

Survey No.92,Gharat wadi,Near Khan Compound, Pelhar,

Vasai East, Mumbai Maharashtra -401208.

Customer Care No.: +91 8780097367

Email : lubxtarindustries@gmail.com

web.www.lubxtar.com

