



LR-45000 GREASE

Premium quality Automotive Grease

PRODUCT DESCRIPTION

LUBXTAR LR -45000 Grease is high performance superior shear resistance grease, hence, has better structural & mechanical stability. This grease has service life of more than 45000 kilometers in automotive bearing application in proper circumstances. This grease is also recommended for roller bearings in axle boxes. It is developed by LUBXTAR's R & D.

APPLICATIONS

Recommended for Wheel Bearings for long haul plying Trucks, all industrial bearings working under high load where chances of contact with water is possible.

FEATURES & BENEFITS

- Excellent shock load carrying ability
- Rust and corrosion inhibited to protect metal surfaces
- Excellent high temperatures capability.
- Oxidation inhibitors permit operations at high temperatures for extended periods of time.

SPECIFICATION & TYPICAL PROPERTIES

Grade	LR-45000	
Mets the following specifications	API NLGI -3,BIS 12203 -87 as well as IS 7623 / 1985	
Typical Properties		
Test Parameters	ASTM Method	Typical values
Colour	Visual	Light Greenish
Structure	Visual	Smooth/Buttery
Soap Type		Lithium
Consistency of the Grease as per Worked Penetration @ 25°C (60 Strokes)	D 217	230 to 250
Drop Point in °C, min	D 566	200
Base Oil Kin. Viscosity @ 100°C,Min	D 445	12.5
Normal Operating Temperature	JPP LM	-20 to 145°C

Manufactured by :

LUBXTAR INDUSTRIES PRIVATE LIMITED

Survey No.92,Gharat wadi,Near Khan Compound, Pelhar,

Vasai East, Mumbai Maharashtra -401208.

Customer Care No.: +91 8780097367

Email : lubxtarindustries@gmail.com

web.www.lubxtar.com

