

TALON AeR

Uniquely designed
for exceptional endurance



Talon AeR is our specially formulated tyre with rich natural rubber tread. It is uniquely designed with apertures to ensure superior resilience and comfort. The Talon AeR tyre is available in black and non-marking tread. Talon AeR comes in grades ranging from Premium Economy to Ultra Premium.

Advantages:

- APERTURES for high endurance and exceptional ride comfort!
- Caters to severe applications with supreme ease
- Excellent wear resistance
- Soft center compound for exceptional heat buildup resistance
- Long tyre life

Talon AeR - Size Range

Tyre Size (Inch)	Tyre Size (Metric)	Rim Size	Tread	TPLA 80	Tyre load capacity on fork lifts, kg at 25kmph	
					Load wheel	Steer wheel
5.00 - 8		3.00	LUG	•	1,415	1,090
6.00 - 9		4.00	LUG	•	1,885	1,450
6.50 - 10		5.00	LUG	•	2,340	1,800
7.00 - 12		5.00	LUG	•	2,920	2,240
8.15 - 15 (28X9 - 15)	225/75-15	7.00	LUG	•	3,445	2,650
8.25 - 15		6.50	LUG	•	4,750	3,650
10.00 - 20		8.00	LUG	•	6,000	5,000
11.00 - 20		8.00	LUG	•	6,000	5,000

• All dimensions are nominal and we reserve the right to make changes any time without notice



TALON AeR - Available Grades

Grade	20	40	40N	50	70
Variant	Black	Black	Non-marking	Black	Black
Design	2-stage rich Natural rubber tread, heat stabilized centre area	3-stage, rich natural rubber tread, soft centre compound	3-stage, rich natural rubber tread, soft centre compound	3-stage, Premium natural rubber tread, extra soft centre compound	3-stage, specially formulated rich natural rubber tread with optimum abrasion resistance
Ride	Firm to Normal	Superior ride comfort	Superior ride comfort	Superior ride comfort	Exceptional ride comfort for continuous extended run
Operating Conditions	Up to 15 hours per day, intermittently	Heavy duty, continuous use	Heavy duty, continuous use	Heavy duty, continuous use	Harsh operating conditions
Advantages	Unique design, exceptional performance for price, ride comfort	Work horse design, low rolling resistance, wide footprint	Work horse design, low rolling resistance, wide footprint	Low rolling resistance, long operating life, wide footprint	Exceptional design to tackle the most severe applications, withstands damage in very rough and abrasive operating conditions, extra wide profile, low rolling resistance and a long operating life.



OneSource™ for all your needs

Corporate Office:

180 Mount Road, Chennai 600 006, India. Phone: **India:** +91 44 4385 7129, **USA:** +1 919 300 7517, **UK:** +44 20 3371 9132 Email: crm@sun-tws.com

Manufacturing locations:

Plant #1
Lot 2, Block B,
Biyagama Export Processing Zone,
Colombo, Sri Lanka.

Plant #2
No. 84, Biyagama Export
Processing Zone, Phase - 2,
Walgama - Malwana, Sri Lanka.

Plant #3
A1-F3/A, New Sidco Industrial Estate,
Maraimalainagar 603 209, India.

Plant # 4
7/B1, Sipcot Industrial Complex,
Pudukottai, Tamil Nadu, India.

Plant # 5
No.06 off M.T.H Road, TVS Complex,
Padi, Chennai - 600 073, India.