VACUUM LEAK TESTER

The Vacuum Leak Tester can be used for checking seal strength of various products like Flexible Pouches / Cups / Blister Packs / Tablet Strip / Sachets / Bottles and many other similar packings. An Acrylic chamber is used so that all sealing area is visible during test and leaks can be detected easily.

The Operational procedure for this machine is very easy to use. Plug the wiring in the electric socket. Switch on the main switch in the equipment. Press the reset button of Timer 1. By pressing of the button the motor start and the needle in the Vacuum Gauge Meter fitted at the top of the equipment starts moving.

Model No. : TBG-760VLTD

SPECIFICATIONS

- Consisting of Transparent Vacuum Chamber made from acrylic.
- Sealed bottle, Pouch keep inside chamber.
- With precise vacuum controller.

TECHNICAL SPECIFICATIONS

✓ Display	:	Digital Model (TBG-760VLTD)
		Analogue Model (TBG-760VLTA)
✓ Vacuum Level Range	:	2mm Hg to 760 mm Hg
✓ Timer Range	:	1 sec to 99 min 59 sec
✓ Power Requirement	:	230 V AC, 50 Hz
✓ Chamber Diameter	:	250mm (300 mm optional)

M/s THE BHARAT GROUP

Regd. Address:
1280, Parvatiya Colony,
New Industrial Town (NIT)
Faridabad-121005, Haryana (IN)

Contact Details:
Tel. : +91 129-2473533, 8130833533
Email: exports@thebharatgroup.com
Web. : www.thebharatgroup.com