



Wheel / Squeeze Grip Type Co2 Fire Extinguisher

FIRE EXTINGUISHER CAPACITY	2kg.Wheel	3kg.Wheel	4.5kg.Wheel	2kg.Squeeze	3kg.Squeeze	4.5kg.Squeeze
MINIMUM PERIOD FOR WHICH THROW OF JET MAINTAINED	8 sec	8 sec	8 sec	8 sec	8 sec	8 sec
MINIMUM PERIOD TO DISCHARGE ATLEAST 90% OF CONTESTS	10 sec	16 sec	20 sec	10 sec	16 sec	25 sec
RANGE OF JET	1 mtr.	1 mtr.	2 mtr.	1 mtr.	1 mtr.	2 mtr.
EMPTY. WT. (APPROX)	6.2kg.	9.5kg.	12.5kg.	6.2kg.	9.5kg.	12.5kg.
FULL WT. (APPROX)	8.2kg.	12.5kg.	17kg.	8.2kg.	12.5kg.	17kg.
FIRE RATING	8B	13B	21B	13B	21B	21B
WORKING PRESSURE	60KGF/CM ²	60KGF/CM ²	60KGF/CM ²	60KGF/CM ²	60KGF/CM ²	60KGF/CM ²
HYDRO PRESSURE	250KGF/CM ²	250KGF/CM ²	250KGF/CM ²	250KGF/CM ²	250KGF/CM ²	250KGF/CM ²
BRUSTING PRESSURE	600KGF/CM ²	600KGF/CM ²	600KGF/CM ²	600KGF/CM ²	600KGF/CM ²	600KGF/CM ²

IS:15683

Trolley Mounted Type Co2 Fire Extinguisher



FIRE EXTINGUISHER CAPACITY	6.5kg.	9kg.	22.5kg.
MINIMUM PERIOD FOR WHICH THROW OF JET MAINTAINED	10 sec	15 sec	20 sec
MINIMUM PERIOD TO DISCHARGE ATLEAST 90% OF CONTESTS	20 sec	36 sec	60 sec
RANGE OF JET	2 mtr.	2 mtr.	2 mtr.
EMPTY. WT. (APPROX)	20kg.	26kg.	43.5kg.
FULL WT. (APPROX)	26.5kg.	35kg.	66kg.
FIRE RATING	N/A	N/A	N/A
WORKING PRESSURE	60KGF/CM ²	60KGF/CM ²	60KGF/CM ²
HYDRO PRESSURE	250KGF/CM ²	250KGF/CM ²	250KGF/CM ²
BRUSTING PRESSURE	600KGF/CM ²	600KGF/CM ²	600KGF/CM ²

IS:2878