

Tpe	Rate output		Voltage	Current	Frequenc	Speed	Efficienc	Power factor	ILR/rated	TLR/Trated	Tmax/Trated	Noise Lw dB(A)
	Kw	HP	V	A	Hz	r/min	%	CosΦ				
80M1-2	0.75	1	380	1.8	50	2830	75	0.84	6.5	2.2	2.3	71
80M2-2	1.1	1.5	380	2.5	50	2830	77	0.86	7	2.2	2.3	71
90S-2	1.5	2	380	3.4	50	2840	78	0.85	7	2.2	2.3	75
90L-2	2.2	3	380	4.7	50	2840	82	0.86	7	2.2	2.3	75
100L-2	3	4	380	6.4	50	2880	82	0.87	7	2.2	2.3	79
112M-2	4	5.5	380	8.2	50	2890	85.5	0.87	7	2.2	2.3	79
132S1-2	5.5	7.5	380	11.1	50	2900	85.5	0.88	7	2	2.2	83
132S2-2	7.5	10	380	15	50	2900	86.2	0.88	7	2.2	2.2	83
160M1-2	11	15	380	22	50	2930	87.2	0.88	7	2	2.2	87
160M2-2	15	20	380	29	50	2930	88.2	0.88	7	2	2.2	87
160L-2	18.5	25	380	36	50	2930	89	0.89	7	2	2.3	87
180M-2	22	30	380	42.2	50	2940	89	0.89	7	2	2.2	92
200L1-2	30	40	380	57	50	2950	90	0.89	7	2	2.2	95

200L2-2	37	50	380	70	50	2950	90.5	0.89	7	2	2.2	95
225M-2	45	60	380	84	50	2970	91.5	0.89	7	2	2.2	97
250M-2	55	75	380	103	50	2970	91.5	0.89	7	2	2.2	97
280S-2	75	100	380	140	50	2970	91.5	0.89	7	2	2.2	99
280M-2	90	120	380	167	50	2970	92	0.89	7	2	2.2	99
315S-2	110	150	380	203	50	2980	92.5	0.89	7	1.8	2.2	104
315M-2	132	180	380	242	50	2980	93	0.89	7	1.8	2.2	104
315L1-2	160	220	380	292	50	2980	93.5	0.89	7	1.8	2.2	104
315L2-2	200	270	380	365	50	2980	93.5	0.89	7	1.8	2.2	104
80M1-4	0.55	0.75	380	1.5	50	1390	73	0.76	6	2.2	2.3	67
80M2-4	0.75	1	380	2	50	1390	74.5	0.76	6	2.2	2.3	67
90S-4	1.1	1.5	380	2.8	50	1400	78	0.78	6.5	2.3	2.3	67
90L-4	1.5	2	380	3.7	50	1400	79	0.79	6.5	2.3	2.3	67
100L1-4	2.2	3	380	5	50	1420	81	0.82	7	2.2	2.3	70
100L2-4	3	4	380	6.8	50	1420	82.5	0.81	7	2.2	2.3	70
112M-4	4	5.5	380	8.8	50	1440	84.5	0.82	7	2.2	2.3	74

132S-4	5.5	7.5	380	11.7	50	1440	85.5	0.84	7	2	2.3	78
132M-4	7.5	10	380	15	50	1440	87	0.85	7	2.2	2.3	78
160M-4	11	15	380	23	50	1460	88	0.84	7	2.2	2.3	82
160L-4	15	20	380	30	50	1460	88.5	0.85	7	2.2	2.2	82
180M-4	18.5	25	380	35	50	1470	91	0.86	7	2	2.2	82
180L-4	22	30	380	43	50	1470	91.5	0.86	7	2	2.2	82
200L-4	30	40	380	57	50	1470	92.2	0.87	7	2	2.2	84
225S-4	37	50	380	70	50	1480	91.8	0.87	7	1.9	2.2	84
225M-4	45	60	380	84	50	1480	92.3	0.88	7	1.9	2.2	84
250M-4	55	75	380	103	50	1480	93	0.88	7	2	2.2	86
280S-4	75	100	380	140	50	1480	93	0.88	7	2	2.2	90
280M-4	90	120	380	164	50	1480	93.5	0.88	7	2	2.2	90
315S-4	110	150	380	201	50	1480	93.5	0.89	7	1.8	2.2	98
315M-4	132	180	380	240	50	1490	94	0.89	7	1.8	2.2	101
315L1-4	160	220	380	289	50	1490	94.5	0.89	7	1.8	2.2	101
315L2-4	200	270	380	361	50	1490	94.5	0.89	7	1.8	2.2	101
90S-6	0.75	1	380	2.3	50	910	72.5	0.7	5.5	2	2.2	65

90L-6	1.1	1.5	380	3.2	50	910	73.5	0.72	5.5	2	2.2	65
100L-6	1.5	2	380	4	50	940	77.5	0.74	6	2	2.2	67
112M-6	2.2	3	380	5.6	50	940	80.5	0.74	6	2	2.2	67
132S-6	3	4	380	7.3	50	960	83	0.76	6.5	2	2.2	71
132M1-6	4	5.5	380	9.4	50	960	84	0.77	6.5	2	2.2	71
132M2-6	5.5	7.5	380	12.6	50	960	85.3	0.78	6.5	2	2.3	71
160M-6	7.5	10	380	17	50	970	86	0.78	6.5	2	2	75
160L-6	11	15	380	25	50	970	87	0.78	6.5	2	2	75
180L-6	15	20	380	31	50	970	89.5	0.81	6.5	1.8	2	78
200L-6	18.5	25	380	45	50	970	89.8	0.83	6.5	1.8	2	78
200L1-6	22	30	380	34	50	970	90.2	0.83	6.5	1.8	2	78
200L2-6	30	40	380	60	50	980	90.2	0.85	6.5	1.7	2	81
225M-6	37	50	380	72	50	980	91	0.86	6.5	1.6	2	87
280S-6	45	60	380	85	50	980	93.5	0.86	6.5	1.6	2	87
280M-6	55	75	380	104	50	980	92	0.86	6.5	1.6	2	88
315S-6	75	100	380	141	50	990	93	0.87	6.5	1.6	2	88

315M-6	90	120	380	169	50	990	93.5	0.87	6.5	1.6	2	88
315L1-6	110	150	380	205	50	990	92	0.87	6.5	1.6	2	89
315L2-6	132	180	380	245	50	990	92.5	0.87	6.5	1.6	2	89
112M-8	2.2	3	380	4.8	50	710	73	0.66	5.5	2	2	63
160M1-8	4	5.5	380	9.9	50	720	84	0.73	6	2	2	69
160M2-8	5	7.5	380	13	50	720	85	0.74	6	2	2	69
160L-87	7.5	10	380	8	50	720	86	0.75	5.5	2	2	72
180L-8	11	15	380	25	50	730	86.5	0.77	6	1.7	2	72
200L-8	15	20	380	34	50	730	88	0.76	6	1.8	2	75
225S-8	18.5	25	380	41	50	730	89	0.76	6	1.7	2	75
250M-8	30	40	380	63	50	730	90.5	0.8	6	1.6	2	88
280S-8	37	50	380	78	50	740	92	0.8	6.5	1.6	2	88
280M-8	45	60	380	93	50	740	92.5	0.8	6.5	1.6	2	89
315S-8	55	75	380	113	50	740	92	0.8	6.5	1.6	2	89
315M-8	75	100	380	152	50	740	92.5	0.81	6.5	1.6	2	89
315L1-8	90	120	380	179	50	740	92.5	0.82	6.5	1.6	2	89
315L2-8	110	150	380	218	50	740	92.5	0.82	6.5	1.6	2	89