

Type	Power	Voltage	Current	Speed	Efficiency	Power factor	LTR/Lrated	TLR/Trated	Noise Lw dB(A)
	Kw	V	A	r/min	%	Cos Φ		Tst/Te	
YD80M 1-4/2	0.45/0.55	380	1.4/1.5	1400/2750	66/65	0.74/0.85	6.5/7	1.5/1.7	79
YD80M 2-4/2	0.55/0.75	380	1.7/2.0	1400/2750	68/66	0.74/0.85	6.5/7	1.6/1.8	79
YD90S-4/2	0.85/1.1	380	2.3/2.8	1410/2830	74/71	0.77/0.85	6.5/7	1.8/1.9	79
YD90L-4/2	1.3/1.8	380	3.3/4.4	1410/2830	76/73	0.78/0.85	6.5/7	1.8/2.0	83
YD100L1-4/2	2/2.4	380	4.8/5.6	1430/2850	78/76	0.81/0.86	6.5/7	1.7/1.9	87
YD100L2-4/2	2.4/3	380	5.6/6.7	1430/2850	79/77	0.83/0.89	6.5/7	1.6/1.7	87
YD112M-4/2	3.3/4	380	7.4/8.6	1445/2890	82/89	0.83/0.89	6.5/7	1.9/2.0	87
YD132S-4/2	4.5/5.5	380	9.8/11.9	1450/2855	83/79	0.84/0.89	6.5/7	1.7/1.8	91
YD132M-4/2	6.5/8	380	13.8/17.1	1450/2880	84/80	0.85/0.89	6.5/7	1.7/1.8	91
YD160M-4/2	9/11	380	18.5/22.9	1460/2920	87/82	0.85/0.89	6.5/7	1.6/1.8	95
YD160L-4/2	11/14	380	22.3/28.8	1455/2920	87/82	0.86/0.90	6.5/7	1.7/1.9	95
YD180M-4/2	15/18.5	380	29.4/36.7	1470/2945	89/85	0.87/0.90	6.5/7	1.8/1.9	95
YD180L-4/2	18.5/22	380	35.9/42.7	1465/2945	89/86	0.88/0.91	6.5/7	1.6/1.8	95
YD200L-4/2	26/30	380	49.9/58.3	1470/2945	89/85	0.89/0.92	6.5/7	1.4/1.6	98
YD225S-4/2	32/37	380	60.7/71.1	1480/2960	90/86	0.89/0.92	6.5/7	1.4/1.6	98
YD225M-4/2	37/45	380	69.4/86.4	1480/2960	91/86	0.89/0.92	6.5/7	1.6/1.6	100

YD250M--4/2	45/52	380	84.4/98.7	1480/2960	91/87	0.89/0.92	6.5/7	1.6/1.6	100
YD280S--4/2	60/72	380	111.3/135.1	1485/2970	91/88	0.90/0.92	6.5/7	1.4/1.5	102
YD280M--4/2	72/82	380	133.6/152.2	1485/2970	91/88	0.90/0.93	6.5/7	1.4/1.5	102
YD90S--6/4	0.65/0.85	380	2.3/2.3	920/1410	64/70	0.68/0.79	6/6.5	1.6/1.4	75
YD90L--6/4	0.85/1.1	380	2.8/3.0	930/1410	66/71	0.7/0.79	6/6.5	1.6/1.5	75
YD100L1--6/4	1.3/1.8	380	3.8/4.4	940/1440	74/77	0.70/0.80	6/6.5	1.7/1.4	78
YD100L2--6/4	1.5/2.2	380	4.3/5.4	940/1440	75/77	0.70/0.80	6/6.5	1.6/1.4	78
YD112M--6/4	2.2/2.8	380	5.7/6.7	950/1430	78/77	0.75/0.82	6/6.5	1.8/1.5	82
YD132S--6/4	3/4	380	7.7/9.5	970/1440	79/78	0.75/0.82	6/6.5	1.8/1.7	82
YD132M--6/4	4/4.5	380	9.8/12.3	970/1450	82/80	0.76/0.85	6/6.5	1.6/1.4	82
YD160M--6/4	6.5/8	380	15.1/17.6	970/1455	84/82	0.78/0.84	6/6.5	1.5/1.5	86
YD160L--6/4	9/11	380	20.6/23.7	970/1460	85/83	0.78/0.85	6/6.5	1.6/1.7	86
YD180M--6/4	11/14	380	25.9/29.8	970/1465	85/84	0.76/0.85	6/6.5	1.6/1.7	90
YD180L--6/4	13/16	380	29.4/33.6	970/1465	86/85	0.78/0.85	6/6.5	1.7/1.7	90
YD200L--6/4	18.5/22	380	41.4/44.9	975/1460	87/86.5	0.78/0.86	6.5/7	1.6/1.5	90
YD225S--6/4	22/28	380	44.2/57.2	980/1470	88/86.5	0.86/0.87	6.5/7	1.8/1.8	92
YD225M--6/4	26/32	380	53.4/65.4	980/1470	88/85.5	0.86/0.9	6.5/7	1.5/1.3	92

YD250M--6/4	32/42	380	62.1/81.1	980/1470	90/86.5	0.87/0.91	6.5/7	1.5/1.3	98
YD280S--6/4	42/55	380	81.5/106.7	985/1480	90/87	0.87/0.9	6.5/7	1.5/1.3	98
YD280M--6/4	55/67	380	106.7/131.5	985/1480	90/87	0.87/0.89	6.5/7	1.6/1.3	98
YD90L--8/4	0.45/0.75	380	1.9/1.8	670/1400	58/72	0.63/0.87	5.5/6.5	1.6/1.4	75
YD100L--8/4	0.85/1.5	380	3.1/3.5	750/1514	67/74	0.63/0.88	5.5/6.5	1.6/1.4	78
YD112M--8/4	1.5/2.4	380	5.0/5.3	710/1430	72/78	0.63/0.88	5.5/6.5	1.7/1.7	82
YD132S--8/4	2.2/3.3	380	7.0/7.1	720/1445	75/80	0.64/0.88	5.5/6.5	1.5/1.7	82
YD132M--8/4	3/4.5	380	9.0/9.4	720/1450	78/82	0.65/0.89	5.5/6.5	1.5/1.6	82
YD160M--8/4	5/7.5	380	13.9/15.2	730/1450	83/84	0.66/0.89	5.5/6.5	1.5/1.6	86
YD160L--8/4	7/11	380	19.0/21.8	730/1450	85/86	0.66/0.89	5.5/6.5	1.5/1.6	86
YD180L--8/4	11/17	380	26.7/32.3	730/1470	87/88	0.72/0.91	6/7	1.5/1.6	90
YD200L1--8/4	14/22	380	33/41.3	735/1470	87/88	0.74/0.92	6/7	1.8/1.7	90
YD200L2--8/4	17/26	380	40.1/48.8	735/1470	87/88	0.74/0.92	6/7	1.5/1.7	92
YD225M--8/4	23/34	380	53.2/66.7	735/1470	89/88	0.77/0.88	6/7	1.5/1.5	92
YD250M--8/4	30/42	380	64.9/78.8	740/1480	90/89	0.78/0.91	6/7	1.6/1.7	94
YD280S-8/4	40/55	380	83.5/102	740/1485	91/90	0.80/0.91	6/7	1.6/1.7	98
YD280M--8/4	47/67	380	96.9/122.9	740/1485	91/90	0.81/0.92	6/7	1.6/1.7	98
YD90S--8/6	0.35/0.45	380	1.6/1.4	675/930	56/70	0.60/0.72	5/6	1.8/2	73

YD90L-8/6	0.45/0.65	380	1.9/1.9	680/920	59/71	0.60/0.73	5/6	1.7/1.8	73
YD100L-8/6	0.75/1.1	380	2.9/3.1	710/945	65/75	0.60/0.73	5/6	1.8/1.9	73
YD112M-8/6	1.3/1.8	380	4.5/4.8	710/945	72/78	0.61/0.73	5/6	1.7/1.9	75
YD132S-8/6	1.8/2.4	380	5.8/6.2	725//970	76/80	0.62/0.73	5/6	1.6/1.9	79
YD132M-8/6	2.6/3.7	380	8.2/9.4	725/970	78/82	0.62/0.73	5/6	1.9/1.9	79
YD160M-8/6	4.5/6	380	13.3/14.7	730/975	83/85	0.62/0.73	5/6	1.6/1.9	83
YD160L-8/6	40702	380	17.5/19.4	730/980	84/86	0.62/0.73	5/6	1.6/1.9	83
YD180M-8/6	7.5/10	380	21.9/24.2	730/980	84/86	0.62/0.73	5/6	1.9/1.9	83
YD180L-8/6	9/12	380	24.7/28.3	730/980	85/86	0.65/0.75	5/6	1.8/1.8	86
YD200L1-8/6	12/17	380	32.6/39.1	735/980	86/87	0.65/0.76	5/6	1.8/2	88
YD200L2-8/6	15/20	380	40.3/45.4	735/980	87/88	0.65/0.76	5/6	1.8/2	88
YD160M-12/6	2.6/5	380	11.6/11.9	480/975	74/84	0.46/0.76	4/6	1.2/1.4	79
YD160L-12/6	3.7/7	380	16.1/15.8	480/975	76/85	0.46/0.79	4/6	1.2/1.4	83
YD180L-12/6	5.5/10	380	19.6/20.5	485/975	79/86	0.54/0.86	4/6	1.3/1.3	83
YD200L1-12/6	7.5/13	380	24.5/26.4	485/975	83/87	0.56/0.86	4/6	1.5/1.5	86
YD200L2-12/6	9/15	380	28.9/30.1	485/975	83/87	0.57/0.87	4/6	1.5/1.5	86
YD225M-12/6	12/20	380	35.2/39.7	490/980	85/88	0.61/0.87	4/6	1.5/1.5	86

YD250M-12/6	15/24	380	42.1/47.1	490/985	86/89	0.63/0.87	4/6	1.5/1.5	89
YD280S-12/6	20/30	380	54.8/58.9	490/990	88/89	0.63/0.87	4/6	1.5/1.5	89
YD280M-12/6	24/37	380	63.7/72.6	490/990	88/89	0.65/0.87	4/6	1.5/1.5	89