



MX260-151A-K-PP

18.000 - 34.000 l/h Discs, cartridges

Typical applications
Plating and process industry

Features

- Service friendly, ideal cleaning access height
- Magnetic drive pump
- Filter chamber with welded bottom (no seal)
- Discs (thin/thick paper, cloth) or cartridges
- All PP construction
- Max. temperature PP 80°C
- Bottom-out or top-out model
- Choice of slurry tank for carbon treatment, mixing and priming
- Unions for rigid piping (PP or CPVC sockets)
- Standard with 3 phase motor, thermal overload switch, lead without plug, pressure gauge, air release and drain valve

Options

- Hose connection
- Dry run protection
- By pass with flowmeter
- Contact manometer
- Single open end cartridges
- Slurrytank
- Sealpump
- Viton



MX260-152A-P-S-PP

Filter Systems series 15

www.hendor.com

Pump	l/h	kW	Union (d/DN)		Hose		Type	Chamber	Medium	Slurrytank	Material
			In	Out	In	Out					
Magnetic drive	16000	0,75	40/32	40/32	1 1/2"	1 1/2"	MX160		K/P	 18 liter 41 liter	PP-EPDM
	20000	1,1					MX210				
	24000	1,5	50/40	50/40	2"	2"	MX260				
	30000*	2,2	63/50	63/50	2 1/2"	2 1/2"	MX350				
	34000*	3					MX410				
* Only with 152A filterchamber							Selection: MX260 151A K PP				

K = cartridges



Qty x L
151A-K = 15 x 10"
152A-K = 15 x 20"

P = discs



Qty OD/ID m²
151A-P = 32 x 280/50 1,9
152A-P = 63 x 280/50 3,8