

PP BALL VALVE - Flange End



TECHNICAL DATA :

CONSTRUCTION : 3 piece design, Single piece stem (Spindle) Reinforced Ball, Teflon seated, full bore.

DESIGN AND MANUFACTURING STD. : As per Manufacturer's Standard

END CONNECTIONS : Flanged as per ANSI B 16.5 (150 #) & as per BS 10 (Table D/E/F) & DIN STD.


AVAILABLE M.O.C. :

PP (POLYPROPYLENE)

HDPE (HIGH DENSITY POLYETHYLENE)

ISOTACTIC PP

PVDF (POLYVINYLIDENE FLUORIDE)



NO.	DESCRIPTION	MATERIAL OPTION	QTY.
01	BODY	PP / HDPE / ISOPP / PVDF	1
02	SIDE PIECE/CONNECTOR	PP / HDPE / ISOPP / PVDF	2
03	BALL	PP / HDPE / ISOPP / PVDF	1
04	STEM/SPINDLE	M.S./S.S. PP/ISOPP/PVDF COATED	1
05	SEAT RING	PTFE	2
06	CONNECTOR SEAL	NEOPRENE RUBBER / PTFE	2
07	STEM SEAL RING	PTFE	1
08	STEM O-RING	NEOPRENE	1
09	STUD, NUT & WASHER	M.S. (EN8) / S.S. 316	REQ.
10	NUT CAP	PP	REQ.
11	HANDLE	M.S. PP COATED	1
12	HANDLE HEX. PIN	M.S. (EN8) / S.S. 316	1
13	HANDLE CAP	PP	1