

PP FOOT VALVE - Screw End



TECHNICAL DATA :

CONSTRUCTION : Ball type, Soft seated

DESIGN AND MANUFACTURING STD. : As per Manufacturer's Standard


END CONNECTIONS : Screw end (BSP thread)

AVAILABLE M.O.C. :

PP (POLYPROPYLENE)

ISOTACTIC PP

PVDF (POLYVINYLIDENE FLUORIDE)



NO.	DESCRIPTION	MATERIAL OPTION	QTY.
01	TOP BODY	PP / ISOPP / PVDF	1
02	BOTTOM BODY	PP / ISOPP / PVDF	1
03	SCREEN	PP / ISOPP / PVDF	1
04	BALL	MS.PP / ISOPP / PVDF COATED	1
05	BALL RING	PP / ISOPP / PVDF	1
06	SEAT RING	NEOPRENE RUBBER	1

ALL DIMENSIONS ARE IN MM (±2 MM)

SIZE		A / F	THDS.	H	T
IN.	MM				
1 "	25	54	1 "	195	22
1 ¼ "	32	54	1 ¼ "	195	22
1 ½ "	40	68	1 ½ "	218	24
2 "	50	78	2 "	218	24
2 ½ "	65	93	2 ½ "	303	29
3 "	80	108	3 "	303	29
4 "	100	135	4 "	377	32