

Super Miniature Capsule Slip Ring



Main Application

- ◆ Electrical test equipment
- ◆ Manufacturing and process control equipment
- ◆ Indexing tables.
- ◆ CCTV pan / tilt camera mounts
- ◆ Robotics, rotary sensors, urgent illumination equipment
- ◆ Exhibit / display equipment.
- ◆ Mini-type wire-rolling machine
- ◆ Closed-circuit control

Contact us to discuss your special needs

LPMS-06B Super Miniature Slip Ring

Description

This unit can be used in any electromechanical system that requires unrestrained, continuous rotation while transferring power or data from a stationary to a rotating structure.

It is also called a rotary electrical interface, commutator, collector, swivel or an electrical rotary joint. It can improve electromechanical capability, simplify system design, eliminate possible damage while rotation. It's the key apparatus of various precision rotary worktable, electric test instrument, manufacture and process control instrument.

The LPMS-06B super miniature slip ring is a standard, Color-coded lead wires are used on both the stator and rotor for simplifying electrical connections.

The LPMS-06B allows tremendous flexibility in dealing with system size restrictions. It is available in 4 and 6 circuit configurations.

Features

- ◆ 6 circuits models
- ◆ 1 amp per circuit, 240 VAC/DC
- ◆ Precision assembly to provide exceptional rotational life
- ◆ Speed up to 100 rpm continuous
- ◆ Precious metals contacts
- ◆ Flexible, color-coded, silver-plated lead wires
- ◆ Superior handling of low level control signals
- ◆ Engineering plastics housing

Advantage

- ◆ Low torque minimizes system torque budget
- ◆ Compact design to fit in the most demanding space.
- ◆ Compact package
- ◆ Low electrical noise
- ◆ Quick shipment per your urgent requirement
- ◆ 360°continuous rotation
- ◆ Addition of special components

Super Miniature Capsule Slip Ring

Specifications

Operating Speed	0-100 rpm
Number of Circuits	6
Voltage	240 VAC/DC
Current Rating	1 amp per circuit
Temperature Range	-20°C to +60°C
Contact Material	Precious metals
Lead Size	30# silver plated copper
Lead Length	Standard 250 mm (9.843inch)
Dielectric Strength	≥500 VAC @50Hz, between each circuit
Electrical Noise	Max 10 mΩ
Housing Material	Engineering plastic

Capsule Length =L

# of Circuits	L (mm)	Part No
6	11.2	LPMS-06B

Contact us on wire color codes

