

## 性能概述:

本粉碎机组采用垂直下出料设备,使某些流动性较差的料粉碎后出料流畅机内无积粉现象。

本机的工作原理是物料进入粉碎室在高速旋转的活动齿盘与固定齿盘受齿的冲击的作用下被粉碎,经筛网筛选后即成为所需的粉料。 本粉碎机组的粉碎机及吸尘器均采用优质不锈钢材料制成,经先进工艺加工粉碎机机壳内壁光滑平整能使出粉更流畅,更便利壳内 清洗工作。高速齿盘与活动牙齿经特种焊接,使活动牙齿坚固耐用安全可靠。本机符合药品生产的"GMP"要求。

## **Applications:**

The Pulverizer Set is adapted the vertical low raw material discharging equipment, it makes some raw materials with poor fluidity after broken can be discharged unblocked and no the phenomenon of accumulated powder.

Its principle of work is as follows: when raw material entered into the crushing chamber, it is broken under the impacting of movable and fixed gear disks that are rotated in high speed and then becomes the needed raw material through screen.

Its Pulverizer and duster are all made of qualified stainless steel. Its inner wall of the housing is smooth and level being processed through superior technology. Therefore it can make the powder discharging more flowing and is benefit to the work of clean too. The gear disk of high speed and movable teeth are welded through special welding, it makes the teeth is durable, safety and reliable. The machine is in conformity with the requirements of "GMP".



## 技术参数 Technical Parameters:

型号 TYPE		
GF20B	GF30B	GF40B
60-150 kg/h	100-300 kg/h	160-800 kg/h
4500 rpm	3800 rpm	3400 rpm
20-120 mesh	20-120 mesh	20-120 mesh
<6cm	< 10 cm	<12 cm
Pulverizer 4 kw	Pulverizer 5.5kw	Pulverizer 11kw
550×600×1250	600×700×1450	800×900×1550
250kg	320kg	550kg
	60-150 kg/h 4500 rpm 20-120 mesh <6cm Pulverizer 4 kw 550×600×1250	GF20B GF30B  60-150 kg/h 100-300 kg/h  4500 rpm 3800 rpm  20-120 mesh 20-120 mesh  <6cm < 10 cm  Pulverizer 4 kw Pulverizer 5.5kw  550×600×1250 600×700×1450