

Water Reducing & Rapid Hardening Admixture

DESCRIPTION

Ultracrete STP-526 is a superior quality **Rapid Hardening Admixture** are an important component of concrete, This Environmental Product Declaration covers hardening admixture. for normal concrete. STP-526 specially developed for. Low Temperature concrete, concrete block and mortar precast and reinforced concrete concrete pipes, electric pol etc..

ADVANTAGES

- 1) Fast Setting
- 2) Super Finishing
- 3) Easily Releasing
- 4) Best Strongness
- 5) Anti Rust (RUST PROOF)
- 6) No Effect Of Wheatear
- 7) Improves workability
- 8) Helps to achive high early strength.
- 9) Reduces shrinkage cracks



DIRECTION FOR USE

Ultracrete STP-526 should be added to concrete / mortar during the mixing cycle at the same time as water is added. Avoid adding to dry cement.

DOSAGE

Field trials should be conducted to determine the exact dosage however a dosage range varying between 150 ml to 500 ml per 50 kg bag of cement can be recommended.

PACKING

Ultracrete STP-526 is available in 220 Kgs packs.

ELECTRIC POL INDUSTRIES



Other admixtures are available

ULTRAMAX India

Corporate office: 2nd floor, L.O. House, near petrol Pump,
(Luv-Kush tower) exhibition road patna-800001
E-mail: info@ultramax@gmail.com
www.ultramax.in