



EMULSI MOULD RELEASE AGENT

Description

Ultracrete MR-D4 is an emulsifying agent to be mixed with diesel to obtain a mould release agent.

Uses

Ultracrete MR-D4 when mixed with diesel functions like a mould release agent and it can be applied to all types of shutters, moulds, steel, timber, plywood, plastic and rubber moulds.

Application Instructions

■ Just mix Ultracrete MR-D4 in diesel in the proportion of 1 ltr MR-D4 to 40 ltrs of diesel. The concentrate can be directly added to the drum containing diesel close to the lid and rolled over to obtain uniformity in mixing. The mixed material is ready to be used as a mould release agent.

Properties

Form : Straw coloured Liquid Specific Gravity : 0.80 to 0.85 at 27°C

Coverage

MR-D4 when mixed with 40 ltr of diesel covers an area of 25 to 50M2/litre when spray applied. On new steel shutters the coverage is about 50M2/litre. In case of plywood and metal shutters better coverage results are obtained by progressive use. When brush applied less coverage is obtained because of evaporation losses.

Packing

Ultracrete MR-D4 is available in 20 ltr and 100 ltr containers.

Shelf Life

MR-D4 has a shelf life of 24 months from the date of manufacture if stored in a cool dry place in original packing.

Health And Safety Instructions

MR-D4 is non toxic and safe.

Disclaimer

Ultramax warrants that all products are free from any defects of manufacture and comply with the specifications given in their respective technical data sheet. No warranty can be given as to the results of use because conditions of use, such as site conditions, surface preparations, workmanship, weather, structural issues and other factors are beyond the control of Ultramax. Purchaser agrees to seek the advice of qualified professionals to carry out tests & take trials to determine the suitability of products for their intended purpose prior to full scale usage of Ultramax products and assumes all risks. The company does not assume any liability for unsatisfactory results, arising from the use of our products. Purchaser's sole liability is limited to replacement of product or refund of the purchase price paid if any product proven defective. No other warranties, express or implied, shall apply including any warranty of erchantability or fitness for a particular purpose. Ultramax shall not be liable for any consequential damages arising from the use of our products for unsatisfactory results. The information supplied in this datasheet is based on our experience through extensive research and is given in good faith in order to help prospective users. We reserve the right to update the information provided in our technical data sheet at any time without prior notice within the scope of technical progress or new developments.

other products categories available

www.ultramax.in