

VISTA NO-3

QUICK SETTING COMPOUND FOR CEMENT MORTARS & CONCRETE ADDITIVES

DESCRIPTION:

A multipurpose quick setting for cement mortar & concrete additive in liquid form when added to concrete, results in quick setting or rapid hardening of the same.

USES:

	An easy to use multipurpose concrete additive. A very useful product for pre-cast Industries where early remoulding is required Very useful for emergency repair in factories during shutdown. It is a highly useful product for stoppage of water ingress through underground structures.				
	In cold weather concreting, it is very useful to set concrete or mortar in sub-zero temperatures				
	For early stripping of shutter to expedite construction work.				
	Sealing joints in masonry, cracks / joints in tunnels etc.				
	Very useful for concrete work during interval of high & low tide when the time is very short for the concrete to set				
ADVANTAGE:					
^	DVANIAGE:				
	It can be used in tunnels, Basement, Emergency Repair and to stop ingress of water through structure in swimming pool, water treatment plant, reservoir etc. It is also used for any emergency repair during short duration of shutdown. For sealing leak joints Vista No.3 is very useful.				

APPLICATION:

Vista No.3 is to be diluted with water in the ratio 1:1 to 1:2. Before addition of diluted Vista No.3, sand, aggregate & cement are to be mixed properly in dry condition. Then the Vista No.3 solution is to be added at last and then mixed quickly, so as to avoid stiffening during mixing. For stopping minor leakages and dampness neat cement and Vista No.3 solution are mixed thoroughly to form a putty like consistency and applied on the surface immediately.



PROPERTIES:

Aspect	Hazy Liquid		
Specific Gravity	1.20 + 0.02		
Dose	1:3 or 4 (Vista No.3 : Cement) but may vary depending on site condition.		
Setting Time	initial	2 to 3 minutes	Variation may occur depending
	Final	4 to 6 minutes	on quality and type of cement.

SHELF LIFE:

18 month from the date of manufacturer, should be stored in a cool and dry place.

PACKING:

Available in 1kg, 5 kg, 10 kg, 20 kg and 250 kg. HDPE Containers

HANDLING PRECAUTION:

Vista No-3 is non-toxic, and ingestion is to be avoided. Any splashes to the skin must be washed with water .If contact with eyes occurs, wash well immediately with water and seek medical advice.

NOTE:

- The contents of the technical data sheet are for general information and guideline only. Results shown here are generated from our laboratory or from our site experiences. This behavior may change as per prevailing condition at the time of application.
- VISTA maintains a team of technical trained professional to provide full support in regards to any of our products.

Manufactured & marketed by

VISTA CHEMTECH PVT. LTD.

(An ISO 9001 Certified Co.)

A SURANA GROUP OF INDUSTRIES

Corporate Office:

Works:

7/1B, Grant Lane, Kolkata – 700 012, (INDIA) T:+91 33 2237 9394 / 2236 0469 / 2215 5513 PO - Jalabishwanathpur, Amta Howrah - 711 322

F: +91 33 2237 9394

 ${\bf E:}$ vista@asuranagroup.com; ${\bf W:}$ www.asuranagroup.com; ${\bf S:}$ asuranagroup

Ankleshwar Balasor Gangtok Howrah Kolkata